

		RECORD	-	· · · C-3	9722		ion of Wate						
						Resources App. No.			Well ID				
1 LOCATION OF WATER WELL:			Fraction				on Number Township Numb						
County													
								treet or Rural Address where well is located (if unknown, distance and rection from nearest town or intersection): If at owner's address, check here:					
Address:													
Address:													
City:		1	State:	ZIP:									
3 LOCAT			ft. 5 Latitude:			(decimal degrees)							
	WITH "X" IN SECTION BOX:						. ft. Longitude:						
	N DUA;	2) ft. 3) ft., or 4) ∐ Dr					Datum: 🗌 WGS 84 🛛 NAD 83 🗌 NAD 27						
	WELL'S STATIC WATER LEVEL:						Source	e for	Latitude/Longitude:				
			 below land surface, measured on (mo-day-yr) above land surface, measured on (mo-day-yr) 						unit make/model:				
NW	NE		Pump test data: Well water was ft.					(WAAS enabled? ☐ Yes ☐ No) ☐ Land Survey ☐ Topographic Map					
wx	Е	-	after hours pumping gpm										
			Well water was ft.										
SW	SE		after hours pumping gpm					6 Elevation:ft. Ground Level TOC					
			timated Yield:gpm re Hole Diameter:in. to ft. an				Source: Land Survey GPS Topographic Map						
S Bore Hole Diameter							Source		Other				
1 mile													
7 WELL WATER TO BE USED AS: 1. Domestic: 5. Public Water Supply: well ID 10. Oil Field Water Supply: lease													
	□ Household												
🗌 Lawn d	Lawn & Garden 7. Aquifer Recharge: well ID						🗌 Ca	ased	Uncased C	Geotechnica	1		
	Livestock 8. Monitoring: well ID						12. Geothermal: how many bores?						
2. 🗌 Irrigati			vironmenta Air Sparge	al Remediation: well I					Loop Horizonta				
3. Feedlo		Extraction											
4. Industrial Recovery Injection 13. Other (specify):													
Was a chemical/bacteriological sample submitted to KDHE? \Box Yes \Box No If yes, date sample was submitted:													
Water well disinfected? □ Yes □ No 8 TYPE OF CASING USED: □ Steel □ PVC □ Other CASING JOINTS: □ Glued □ Clamped □ Welded □ Threaded													
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Infreaded Casing diameter in. to ft., Diameter ft., Diameter ft., Diameter													
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No													
TYPE OF SCREEN OR PERFORATION MATERIAL:													
□ Steel □ Stainless Steel □ Fiberglass □ PVC □ Other (Specify)													
Brass Galvanized Steel Concrete tile None used (open hole)													
SCREEN OR PERFORATION OPENINGS ARE:													
Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)													
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft. to ft. to ft.													
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft. o ft. o ft. o ft. ft. to ft. to ft. ft. to ft. ft. ft. ft. ft. ft. ft. ft. ft													
Grout Intervals: From													
		le contaminatio		,			,						
Septic			lateral Line				ivestock Pe		Insectic				
Sewer]			Cess Pool Seepage Pit				uel Storage		Abando		Well		
U Watert	ight Sewer Li	ines 🗆 S	seepage Pit	☐ Feedyard		\Box F	ertilizer Sto	orage	🗌 Oil Wel	I/Gas Well			
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well □ Other (Specify) Distance from well? ft.													
10 FROM	TO		ITHOLO		FRO		TO	LIT	HO. LOG (cont.) or	PLUGGIN	G INTERVALS		
					Notes	:							
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged													
under my jurisdiction and was completed on (mo-day-year)													
Kansas Water Well Contractor's License No													
under the business name of													
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.													
-		eks.gov/waterwell		, ater, Geology Stelloll, I	JUD D IT JAC		, 5uite 420,	rope	, Fu isas 00012-130		A 82a-1212		