


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Cloud Fraction: NE 1/4 SE 1/4 SW 1/4 Section Number: 15 Township Number: 6 Range Number: 5 Distance and direction from nearest town or city street address of well if located within city: 5 miles south Jamestown KS

2 WATER WELL OWNER: Wayne Holton RR#, St. Address, Box #: PO Box 224 City, State, ZIP Code: Jamestown, KS 66948 Board of Agriculture, Division of Water Resources Application Number: 11A

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 11A ft. Depth(s) Groundwater Encountered 1. 23 ft. 2. 20 ft. 3. 8-25-17 ft. WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 8-25-17 Pump test data: Well water was 18 ft. after 2 hours pumping 20 gpm Est. Yield 50 gpm: Well water was 18 ft. after 2 hours pumping 20 gpm Bore Hole Diameter 10 in. to TID ft. and 10 in. to TID ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted No Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter 5 in. to 20 ft. Dia. 18 in. to 20 ft. Dia. 500 lbs./ft. Wall thickness or gauge No. 26 Casing height above land surface 18 in. weight 500 lbs./ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 40 ft. to 20 ft. From 40 ft. to 20 ft. GRAVEL PACK INTERVALS: From 40 ft. to 20 ft. From 40 ft. to 20 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 20 ft. to 0 ft. From 20 ft. to 0 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? NW How many feet? 800

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-25-17 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 608 This Water Well Record was completed on (mo/day/yr) 12-19-17 under the business name of Yellow Jacket Drilling by (signature) W. J. Hall

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

T

D

EW

SEC.

1/4

7/4

 $\frac{1}{2}$