


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: MITCHELL		NW 1/4 NE 1/4 NE 1/4	36	T 6 S	R 8 E (W)
Distance and direction from nearest town or city street address of well if located within city? 3 W OF BELOIT					
0 MW -2-92					
2 WATER WELL OWNER: MITCHELL CO HWY DEPT					
RR#, St. Address, Box #: BOX 8					
City, State, ZIP Code: BELOIT, KS 67420					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 19 ft. ELEVATION: 1478.2			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 4.18 ft. below land surface measured on mo/day/yr 9/27			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 5 SEE BELOW ft., and in. to ft.			
WELL WATER TO BE USED AS:					
5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter 2 in. to 12 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface 3 FT in., weight lbs./ft. Wall thickness or gauge No. SC 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 19 ft. to 12 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 19 ft. to 10.5 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 10.5 ft. to 0 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? W How many feet? 50					
LANDFILL					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
INSTALLED 2 IN LINER					
WELL INSIDE EXISTING					
5 IN PVC WELL					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/27/94 and this record is true to the best of my knowledge and belief. Kansas					
Water Contractor's License No. 537 This Water Well Record was completed on (mo/day/yr) 12-31-94					
under the business name of AGD Services Inc by (signature) Keith Greiner					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4