

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Osborne	SE 1/4 SW 1/4 SW 1/4	13	T 7 S	R 13 E/W

Distance and direction from nearest town or city street address of well if located within city?

Approximately 1/2 mile west of Osborne

2 WATER WELL OWNER:	Osborne, City of c/o City Clerk 133 West Main Osborne, KS 67473	Board of Agriculture, Division of Water Resources Application Number: 37,012
---------------------	--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 41 ft. ELEVATION: unknown
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 10. ft. below land surface measured on mo/day/yr 8-16-91
	Pump test data: Well water was not ch'd. ft. after hours pumping gpm
	Est. Yield unknown gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter . . . 18. in. to . . . 41. ft., and in. to ft.	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes. No. X. If yes, mo/day/yr sample was submitted Drilled near existing well Water Well Disinfected? Yes X No	

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 8. in. to 29. ft., Dia 8. in. to 40. ft., Dia in. to ft.	Casing height above land surface 12. in., weight 5.54 lbs./ft. Wall thickness or gauge No. 322		
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 29 ft. to 36 ft., From ft. to ft.		From ft. to ft., From ft. to ft.	
GRAVEL PACK INTERVALS: From 25 ft. to 41 ft., From ft. to ft.		From ft. to ft., From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	Dirt	3 Bentonite	4 Other Bentonite Holeplug & Sand
Grout Intervals: From 4 ft. to 21 ft., From 0 ft. to 4 ft., From 21 ft. to 25 ft.	What is the nearest source of possible contamination: (FOR PILES UNIT)				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
			13 Insecticide storage	None known	
Direction from well?			How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	Topsoil, clay			
7	18	Sand and gravel, medium			
18	26	Clay			
26	28	Sand and gravel with clay			
28	36	Sand and gravel, fine, medium			
36	41	Dakota shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-16-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 9-27-91 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke Well & Equipment</i>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.