WATE	R WE	LL RECORD	Form \	WWC-5	Division of Wa	ter Resources App. N	o	
		OF WATER WELL:	Fraction		Section Number	Township No.	Range Number	
	nty: OS			W 1/4 SE 1/4		T 7 S		
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here								
Iron	n nearest	town or intersection: If at	owner's address, che	Latitude: (in decimal degrees) Longitude: (in decimal degrees)				
				Elevation: (in decimal degrees)				
A WATER WELL OWNER					<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: GERELYN A. CARLIN RR#, Street Address, Box #: 1606 W. 70TH DRIVE					Collection Method:			
RR#, Street Address, Box #: 1606 W. 70TH DRIVE City, State, ZIP Code : OSBORNE, KS 67473				☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
City	, state, z	OSBOF	(NE, KS 6/4/3			<3 m, 3-5 m,		
3 LOCATE WELL 60								
	TH AN "X	WXX IN 4 DEPTH OF COMPLETED WELL 60 ft.						
SEC	TION BO N	1 1 1						
F	Pump test data: Well water was AIR DEV ft. after hours pumping gpm							
	EST. YIELD. 2gpm. Well water was							
w N	w T E Bore Hole Diameter 11.5 in. to .20							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
s	cw cE \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well ☐ Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No								
S If yes, mo/day/yr sample was submitted								
Water well disinfected? ✓ Yes □ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: 7 Glued Clamped Welded Threaded								
Casing diameter 5 in to 30 ft., Diameter 5 in to 50 ft., Diameter in to ft.								
Casing height above land surface. 12 in., Weight								
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
□ Louvered shutter □ Key punched □ Wire wrapped ☑ Saw cut □ Other (specify) SCREEN-PERFORATED INTERVALS: From .30 ft. to .40 ft., From .50 ft. to .60 ft.								
From ft. to ft.								
GRAVEL PACK INTERVALS: From 20 ft. to 60 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ✓ Bentonite ☐ Other								
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Septic tank								
		ht sewer lines 🔲 Seepage p		Fertilizer st				
		n well				OC () PIV		
FROM 0	30	LITHOLOG	IC LOG	FROM	TO LITHO. I	LOG (cont.) or PLU	GGING INTERVALS	
30	35	CLAY W/ BROKEN LIN	MESTONE					
35	50	CLAY	ILOTONE			· · · · · · · · · · · · · · · · · · ·		
50	55	CLAY W/ BROKEN LIN	MESTONE					
55	60	GRAY SHALE						
ļ							-	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, □ reconstructed, or □ plugged								
under my jurisdiction and was completed on (mo/day/year) .09/11/2012 and this record is true to the best of my knowledge and belief								
Kansas Water Well Contractor's License No. 741 This Water Well Record was completed on Imo/day/year 1 09/13/2012								
under the business name of WATSON WELL DRILLING by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at								
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212								
NOA 828	-1212	1/17/1	1		Check: [✓] W	mie copy, 🛂 Blu	ie Copy, 🔲 Pink Copy	

741