WATE	R WEI	L RECORD	Form WV	VC-5	Division of Water	Resources App. No) <u>.</u>	
1 LOC	ATION	OF WATER WELL:	Fraction				Range Number	
	ty: Roo		NW ¼ NW ¼ NW			T 7 S	R 18 □E 🗹 W	
		Address of Well Location;		Global Positioning				
from nearest town or intersection: If at owner's address, check here .					Latitude:			
From Stockton, Ks. 1 mile south, 3 1/2 west					Longitude: (in decimal degrees) Elevation:			
					Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Steve Felhoelter					Collection Method:			
RR#, Street Address, Box #: 1695 Y Road					GPS unit (Make/Model:)			
City, State, ZIP Code : Plainville. Ks 67663					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .45					ft.			
SECT	TION BOX: Depth(s) Groundwater Encountered (1).16. ft. (2). ft. (3). ft.							
	N WELL'S STATIC WATER LEVEL15							
X	ECT VIELD 15 cmm Well water was A after house manning come							
w NV	1 NW-1-NE-1 D 111 D: 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							
" _	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
CN	Oil field water supply Dewatering Other (Specify below)							
3	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No								
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? ☑ Yes □ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5								
Casing height above land surface. 24 in., Weight 2.91 lbs./ft., Wall thickness or gauge No21 TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
	Brass	Galvanized Steel		le)	() ,			
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From .45 ft. to20 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other								
Grout Intervals: From .20								
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
	Sewer lin			Fuel storage			a (specify delow)	
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
		n well						
FROM	TO	LITHOLOG	IC LOG	FROM	TO LITHO. LC	OG (cont.) or PLU	GGING INTERVALS	
0	10	Fine Sand						
10 16	16 31	Gumbo Clay Sand & gravel						
31	45	Shale						
	70	Ondie						
· · · · · · · · · · · · · · · · · · ·								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, □ reconstructed, or □ plugged								
under my jurisdiction and was completed on (mo/day/year) .4/18/14 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 0199 This Water Well Record was completed on (mo/day/year) 5/2/14 under the business name of Karst Water Well Drilling & Service, Inc. by (signature)								
INSTRUC	TIONS	Use typewriter or ball point pen	PLEASE PRESS FIRMIV	and PRINT of	. Dy (Signature)	and check the some	mounter Sandan James	
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers, send on copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								

http://www.kdheks.gov/waterwell/index.html