ces	
ft.	유
pm	CE (
pm	FFICE USE ONL
ft.	NLY
ow)	
 as	
_ft.	
	-
e)	
	E
ft.	
ft. ft.	ᅍ
ft.	
ft.	
٠٠ ال	
	S
] ່ຕ່

LI CONTION OF WATER WITH	WATER WELL RECORD Form		12 ID No. 003/1115		
1 LOCATION OF WATER WELL:	Fraction	Section Number		Range Number	
			т 07 s	R 02 W	
Distance and direction from nearest tow 291 E. Main St	vn or city street address of well if located with	in city?			
2 WATER WELL OWNER:	KDHE				
RR#, St. Address, Box # :	1000 SW Jackson Suite 410		Board of Agriculture, Div	ision of Water Resources	
City, State, ZIP Code :	Topeka, KS 66612		Application Number:		
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:				27 (TOC)	
A X	Depth(s) Groundwater Engagetered 1		2 4	2 #	
	Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 24.	23	Z	3-28-06	
NW NE					
₩ W E	Pump test data: Well water w				
¥ W E	Est. Yield gpm: Well water w	asft	. after hours r	oumpinggpm	
	Bore Hole Diameter 8.5 in. to WELL WATER TO BE USED AS: 5 Pub 1 Domestic 3 Feed lot 6 Oil fi	25	ft. and ir	n. toft.	
sw se	WELL WATER TO BE USED AS: 5 Publ	ic water supply	8 Air conditioning 1	1 Injection well 2 Other (Specify below)	
	1 Domestic 3 Feed lot 6 Oil i	eid water supply	9 Dewatering	2 Other (Specify below)	
S	2 Irrigation 4 Industrial 7 Law				
	Was a chemical/bacteriological sample sub				
	submitted	Wat	er Well Disinfected? Yes	No X	
5 TYPE OF BLANK CASING USED:	5 Wrought Iron	8 Concrete tile	CASING JOINTS: Glue	d Clamped	
1 Steel 3 RMP (
2 PVC 4 ABS	7 - 1		774	aded Flush	
	•	in to			
Costs being diameter 2	in. to 10 ft., Dia	In. to	π., Dia	- In. to	
Casing neight above land surface FI	lushmount in., weight 0.	lbs./ft.	Wall thickness or gauge No.	3011.40	
TYPE OF SCREEN OR PERFORATION		7 PVC	10 Asbestos-ceme	ent	
1 Steel 3 Stainle	ess steel 5 Fiberglass nized steel 6 Concrete tile	8 RMP (SR)	11 Other (specify)12 None used (op		
2 Brass 4 Galvar	nized steel 6 Concrete tile	9 ABS	12 None used (op	en hole)	
SCREEN OR PERFORATION OPENIN		wrapped	8 Saw cut	11 None (open hole)	
	Mill slot 6 Wire wra	apped	9 Drilled holes		
2 Louvered shutter 4		ıt	10 Other (specify)		
SCREEN-PERFORATED INTERVALS:					
	From ft. to	ft. F	rom ft.	toft.	
GRAVEL PACK INTERVALS:		25 ft. F	rom ft.	to ft.	
,	From ft. to	ft. F	rom ft.	to ft.	
6 GROUT MATERIAL 1 Neat of	cement 2 Cement grout	3 Rentonite	4 Other		
What is the nearest source of possible of	ft. to 8 ft. From				
1 Septic tank		10 Livest	ock pens 14 Ab	Lucil/ Con unil	
	4 Lateral lines 7 Pit privy	11 Fuels	storage 15 Oi	well/ Gas well	
	5 Cess pool 8 Sewage la			itier (specify below)	
3 Watertight sewer lines	6 Seepage pit 9 Feedyard		ticide storage		
Direction from well?	LITHOLOGIC LOC	How many		NTEDVALS	
FROM TO CODE TO	LITHOLOGIC LOG	FROM TO	PLUGGING I	INIERVALO	
	, red brown, unconsolidated dirt,				
	ii, red brown, unconsolidated dirt, ivel, glass/trash, wood debris				
	ay, stiff, med to high plasticity,				
	ocky, red brown				
	ind, fine to med grain, well sorted,				
	ange brown to red brown				
	aystone, very stiff, high plasticity,				
	ocky, mottled red and light gray				
7 CONTRACTOR'S OR LANDOWNER	R'S CERTIFICATION: This water well was	1) constructed, (2) reco	nstructed, or (3) plugged und	der my jurisdiction and was	
2 29 06					
Water Well Contractor's License No. 531 This Water Well Reford was completed on (molday/yr) 4-14-06					
under the business name of Geotechnical Services, Inc. by (signature)					
	s and circle the correct answers. Send three co	by (signature) U	of Health and Environment		
	as 66612-1367. Telephone: 913-296-5545. Ser				