WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 00371122

1 LOCATION OF WATER WELL:			Fraction				Sect	on Number	r Town	ship Number	Rar	nge Number	
			NW		NE	% NW	14	15	Т	07 s	- 1	· !	w
			town or city stre						<u>'</u>		1		
	291 E. Main												
2 WATER	WELL OWNE	R:	KDHE										
RR#, St. Ad	ldress, Box#	:	1000 SI	N Jaci	kson S	uite 410			Board (of Agriculture,	Division of W	ater Resou	rces
City, State,	ZIP Code	_:_	Topeka	, KS (66612				Applica	tion Number:			
LOCATE	WELL'S LOC	CATON W	ITH 4 DEDTU				26				DE 20 (TO	C) .	
	N SECTION B	OX:	DEPTH	OF COI	MPLETEL	WELL	20	M. ELE	:VATION:		33.30 (10	٠,	
	ı^		Depth(s) G	roundwa	iter Encou	intered 1	20	1	ft. 2	!	ft. 3	2 20 00	^{π.}
	NW	- NE	WELL'S ST							sured on mo/			
<u> </u>	i I		_							hou			
± W		$\overline{}$	E Est. Yield		gpm:	Well water v	vas		ft. after	hoe	urs pumping		gpm
		<u> </u>	Bore Hole	Diamete	r 8.5	in. to	26		ft. and		in. to		ft.
	sw	- SE	1 Do	nestic	3 Feed !	ot 6 Oil	olic water su field water s	ippiy :unniv	9 Dev	onditioning atering	11 Injection	on well (Snecify bel	ow)
l L			1									(Opcony bo	···/
	S		1							nitoring well			
			1	mical/ba	cteriologic	al sample su	bmitted to L			No X If			vas
51		·	submitted							sinfected? Ye			
	F BLANK CAS				-					IG JOINTS: (Clamped	
1 Ste		_	MP (SR)			tos-Cement			-		Velded		
2 PV		4 AE			7 Fiberg	lass				<u>L</u>	hreaded	Flush	\blacksquare
Blank casing	g diameter	2	in. to	11	ft., D	ia	in. to		ft., Dia		in. to		ft.
Casing heig	ht above land	surface	Flushmou	i nt in.	, weight	0.	703	lbs./ft	. Wall thickr	ness or gauge	No.	Sch. 40	
TYPE OF S	CREEN OR P	ERFORA	TION MATERIA	L:	,			PVC	1	0 Asbestos-c	ement		
1 Ste	el	3 St	ainless steel		5 Fiberg	lass	8		1	1 Other (spe	cify)		
2 Bra			alvanized steel		6 Concre	ete tile	9	ABS	1	2 None used	(open hole)		. [
SCREEN O	R PERFORAT	_	NINGS ARE:							cut	11 Nor	ne (open ho	le)
1 Cor	ntinuous slot		3 Mill slot			6 Wire wr			9 Drille				
2 Lou	evered shutter		4 Key punche			7 Torch o			10 Othe	r (specify)			
SCREEN-PI	ERFORATED	INTERVA	LS: From	1	<u>1</u>	ft. to	26	ft.	From		ft. to		ft.
			From			ft. to		ft.	From		ft. to		ft.
GR/	AVEL PACK II	NTERVAL	S: From	9	9	ft. to	26	ft.	From		ft. to		ft.
			From			ft. to		ft.	From		ft. to		ft.
6 GROUT	MATERIAL:	1 No	eat cement	2 C	ement gro	out	3 Ben	onite	4 Other				
			ft. to										
l			ble contamination		••				stock pens	14	Abandoned	water well	.
1	ptic tank	•	4 Lateral			7 Pit privy			storage		Oil well/ Ga		
2 Se	wer lines		5 Cess p			8 Sewage la		12 Fert	tilizer storag		Other (spec		
3 Wa	atertight sewer	lines	6 Seepag	ge pit		9 Feedyard		13 Inse	ecticide stora	ige			
Direction fro	om well?							How man	ny feet?				
FROM	ТО	CODE		THOLO	GIC LOG		FROM	ТО		PLUGGIN	NG INTERVA	LS	
0	0.25		Asphalt		** **								
0.25	5.5		Clay, stiff, hi		sticity, sr	nali gravel							
0.25	5.5	СН	inclusions, but Clay, with si		to high	daeticity			-				
5.5	10	СН	red brown	ii, iiloū	to mgn j	Jiasucity,							
	† 		Silty Sand,	verv fir	ne to fine	grain. well			1				
10	20	SP-SM	sorted, orang			J, J.							
			Sand, fine to			l sorted,							
20	26	SP	orange brown	to dar	k gray			ļ					
									1				
								-	-				
	-									WI			
7 CONTE	ACTORIC OF	LANDO	(NED'S OFFI	ICATIO:	Ni. This	ntagrealt -	(4) comits	tod (0) ==	nonotract at	or (2) -l	Lundor	indiatiA-	1 4400
			NER'S CERTIF										
1 .	on (mo/day/yr)			J-28-	UD		and th	is record is	true to the	best of my kno	owledge and	belief. Kan:	sas
1		icense No)		531				Record was	completed on	(mo/day/xr)	/4-14-	<u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>
	usiness name		Geotech				by (sig	nature)	يبير	Mon	W	Hotel Accord	2101
			planks and circle t									water, 1000	2 W