

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Cloud	SW $\frac{1}{4}$ SE $\frac{1}{4}$ SW $\frac{1}{4}$	10	T 07 S	R 02 W

Distance and direction from nearest town or city street address of well if located within city?

Northwest corner of intersection Main St. and Second St., Aurora

2 WATER WELL OWNER:	KDHE
RR#, St. Address, Box # :	1000 SW Jackson Suite 410
City, State, ZIP Code :	Topeka, KS 66612
Board of Agriculture, Division of Water Resources	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	25 ft. ELEVATION:	92.83 (TOC)
	Depth(s) Groundwater Encountered 1	23 ft.	2 ft.
	WELL'S STATIC WATER LEVEL	15.01 ft. below land surface measured on mo/day/yr	05/16/07
	Pump test data: Well water was	ft. after	hours pumping
	Est. Yield gpm: Well water was	ft. after	hours pumping
	Bore Hole Diameter	8.5 in. to	25 ft. and
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feed lot	6 Oil field water supply	9 Dewatering
2 Irrigation	4 Industrial	7 Lawn and garden (domestic)	10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes	No X	If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes	No X		

5 TYPE OF BLANK CASING USED:	5 Wrought Iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded
Blank casing diameter	2 in. to	10 ft., Dia		ft.
Casing height above land surface	Flushmount	in., weight	0.703 lbs./ft.	Wall thickness or gauge No. Sch. 40
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From 10 ft. to	25 ft. From		
GRAVEL PACK INTERVALS:	From 8 ft. to	25 ft. From		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals	From 1.5 ft. to	8 ft. From		
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/ Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?	How many feet?			

FROM	TO	CODE	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	CL	Clay, with silt, dark brown			
5	15	CL	Clay, with silt, light brown			
15	20	SP	Sand, with clay			
20	25	CL	Clay, gray with purple patches			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was	(1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr)	08/06/07	and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No.	531	This Water Well Record was completed on (mo/day/yr)	09/06/07
under the business name of	Geotechnical Services, Inc.	by (signature)	

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.