	057112	w	ATER WELL RE	CORD Fo	orm WWC-5	KSA 82a-12	212 ID No. 0	0379607	N	/IW-19
LOCATION OF	WATER WELL	.: Fraction			Sect	ion Number			Range Num	nber
ounty:	Cloud	NW	% NE	_{1/2} NW	1 1/4	15	т 07		R 02	w
		est town or city street								
outh of inters	section Mair	St. and Second	St., Aurora							
WATER WELL	OWNER:	KDHE								
R#, St. Address,		1000 SW	Jackson S	uite 410			Board of Ag	riculture, Divis	sion of Water Re	sources
ty, State, ZIP Co	de :	Topeka,	KS 66612				Application			
LOCATE WELL	'S LOCATON	WITH ,							(700)	
AN 'X" IN SEC	TION BOX:	DEPTH C	F COMPLETE	WELL	24	ft. ELEV	/ATION:	95.6	2 (TOC)	
X		Depth(s) Gro	undwater Enco	intered 1	17	ft.	. 2	ft.	3	 ft.
NW-	NE								r 05/16/	
		P	ump test data:	Well wate	rwas	fi	t. after	hours p	umping	gpm
w	+	E Est. Yield	gpm:	Well wate	r was	fi	t. after	hours p	umping	gpm
į		Bore Hole Dia	ameter 8.	in. to	24	<u> </u>	ft. and	in.	to Injection well Other (Specify	ft.
sw	SE	WELL WATE	R TO BE USED) AS: 5 P	ublic water s	apply	8 Air condi	tioning 11	Injection well	
		Dome	estic 3 reed		ii field water	supply	9 Dewater	ng 12	Other (Specify	below)
	S	1								
			cal/bacteriologi	al sample :	submitted to I				mo/day/yr samp	
	·	submitted				Wa	ter Well Disinfe	cted? Yes	No X	
TYPE OF BLA			•	ht Iron	8 Concr	ete tile	CASING J	DINTS: Glued	I Clamp	oed
1 Steel	3	RMP (SR)	6 Asbes	tos-Cemen	t 9 Other	(specify belo	w)	Weld	ed	
2 PVC	4 /		7 Fiberg	lass				Threa	ded Flu	sh
ank casing diam	eter 2	in. to	9 ft., D	ia				<u> </u>	in. to	ft
sing height abo	ve land surface	Flushmoun	t in weight		0.703	lbs./ft.	Wall thickness	or gauge No.	Sch. 4	40
		ATION MATERIAL:					10 A			
1 Steel	3	Stainless steel	5 Fibero	lass						
2 Brass	4	Galvanized steel			9	ABS	12 N	one used (ope	n hole)	
CREEN OR PER	FORATION OF	PENINGS ARE:		5 Gauz	ed wrapped		8 Saw cut		11 None (open	n hole)
1 Continuou	ıs slot	3 Mill slot		6 Wire	wrapped		9 Drilled hol	es		
2 Louvered	shutter	4 Key punched		7 Torch	ı cut		10 Other (sp	ecify)		
CREEN-PERFO	RATED INTER	VALS: From	9	ft. to	24	ft. F	rom	ft. t	0	ft
									0	
GRAVEL	PACK INTERV		8	ft. to	24	ft. F	From	ft. t	0	ft
		From		ft. to		ft. F	rom	ft. t	0	ft
GROUT MATE	RIAL: 1	Neat cement	2 Cement or	out	3 Ber					
		ft. to			#	to.	# From		# to	 fi
hat is the neares	et source of nos	sible contamination		"	''.	10 Lives	tock name	14 Ab	andoned water v	المهر المهر
1 Septic tar		4 Lateral lin		7 Pit privy	,	11 Fuel	•		well/ Gas well	WC:
2 Sewer line		5 Cess poo		8 Sewage			izer storage		ner (specify belo	w)
3 Watertigh		6 Seepage		9 Feedya	-		cticide storage	10 00	ici (specii) beio	•••,
rection from well		- coopingo				How many				
	O CODE	LITE	HOLOGIC LOG		FROM	TO		PLUGGING IN	NTERVALS	
0 0	.5	Asphalt								
	0 CL-M	L Silty Clay, lig	ht brown							
	l3 sw	Sand, with mi	nimal clay							
13 2	24	Sandstone, t	ine grained							
		 								
		+								
							1			

531

Geotechnical Services, Inc.

This Water Well/Re

INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

Water Well Contractor's License No.

under the business name of

grd was completed or (mo/day/y

09/06/07