			W	ATER WELL REC	ORD Form	1 WWC-5	KSA 82a-	1212 ID No	
1 LOCATIO		_		» NW	Alul		on Numbe		B
County:			NW			1/4	34	T	R 22 EW
CROS. M.	ke Scott)	town or city stree	t address of well	if located wit	hin city?			
2 WATER V	WELL OWNE	R: RA	er Jones					}	
RR#, St. Add	íress, Box#	: 2	oak Cir	ule, .				Board of Agriculture	, Division of Water Resources
City, State, Z	IP Code	1	Ke Dallas	TV 75065				Application Number:	
3 LOCATE	WELL'S LOC SECTION B	CATON WI	THI 4 DEPTH	OF COMPLETED	AATTI I	60	A 515	NATION.	
		UX.	Derinc	OF COMPLETED	VVELL		R. ELE	EVATION:	A A
	N		Depth(s) Gro	undwater Encou	nterea 1			π. 2	ft. 3ft.
1 17									/day/yr
		NE							urs pumping gpm
	i	i	Est. Yield	gpm:	Well water w	vas		ft. after ho	urs pumpinggpm
₹ w			E Bore Hole Di	ameter 8	in. to	60		ft. and	in. to ft. 11 Injection well 12 Other (Specify below)
ī	i 1	·	WELL WATE	R TO BE USED	AS: 5 Put	dic water su	pply	8 Air conditioning	11 Injection well 12 Other (Specify below)
	sw	SE	2 1-1-20	tion 4 Industr	n 001	meru water s	uppiy	5 Dewatering	12 Other (Specify below)
1	~	i 1	1						
ч	S		1	ical/bacteriologic	al sample su	bmitted to D			f yes, mo/day/yr sample was
			submitted					ater Well Disinfected? You	
	BLANK CAS				ht Iron				Glued X Clamped
_1_Stee	el	3 RM	IP (SR)	6 Asbest	os-Cement	9 Other (specify be	ow)	Welded
2 PVC		4 AE	S	7 Fibergi	ass				Threaded
Blank casing	diameter	4.5	in. to	40 ft., Di	а	in. to)	ft., Dia	in. to ft.
Casing heigh	nt above land	surface	18	in., weight	2	.38	ft.adl	. Wall thickness or gauge	No248
TYPE OF SO	CREEN OR P	ERFORA	TION MATERIAL			171	PVC:	1/3 Achaetae	cement
1 Stee	ei	3 Sta	ainless steel	5 Fibergl	ass	8	RMP (SR)	11 Other (spe	cify)
2 Bras	S8	4 Ga	Ivanized steel	6 Concre	ite the	9 /	ABS	12 None used	cify) I (open hole)
SCREEN OF	R PERFORA	TION OPE	NINGS ARE:		5 Gauzeo	l wrapped		8 Saw cut	11 None (open hole)
	ntinuous slot		3 Mill slot		6 Wire wr	apped		9 Drilled holes	
2 Lou	vered shutter	r	4 Key punched		7 Torch o			10 Other (specify)	
SCREEN-PE	ERFORATED	INTERVA	LS: From	40	ft. to	60	ft.	From	ft. toft.
			From		ft. to		ft.	From	ft. toft.
GR/	AVEL PACK I	NTERVAL		20	ft. to	60	ft.	From	ft. toft.
			From		ft. to		ft.	From	ft. to ft.
6 GROUT	MATERIAL:	1 No	eat cement	2 Cement are	urt	3 Bent	onite	4 Other	
Grout Interva	als From	0	ft. to 2	0 ft. From	•	ft. to		ft. From	ft. toft.
What is the	nearest source	e of possi	ole contamination	1			10 Live	stock pens 14	Abandoned water well
								5 Oil well/ Gas well	
	ver lines							ilizer storage 16	
	tertight sewer	rlines	6 Seepage		9 Feedyard	•		cticide storage	(,
Direction fro	-						How man		none
FROM	TO	CODE	LIT	HOLOGIC LOG		FROM	ТО		NG INTERVALS
0	2		surface						
2	4		Loess						
4	16		Fine to med	sand					
16	60		Grey shale						
							ļ		
							 		
							ļ		······································
							1	.	
		ļ							
							ļ		
7 ICOLITE	OTODIC OF	LANGO	NED'S OFFITH	ATION! This	tordl	(1)	nd (0) ==	meta inted as (2) almost d	under my installation and
									under my jurisdiction and was
completed o	n (mo/day/yr)		6-14-06		and thi	s record is	true to the best of my kno	owledge and belief. Kansas (mo/day/yr) 6-14-06
Water Well (Contractor's I	License No						•	
under the bu	siness name	of	Wo	ofter Pump	& Well In	ic.			uy 6 W 80/100
INSTRU	JCTIONS: Plan St. Ste 420	ease fill in b Toneka K	lanks and circle the	correct answers.	Send three co	pies to Kansa nd one to WA	as Departm	ent of Health and EnvironMe OWNER and retain one for	nt, Bureau of Water, 1000 S W