WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL: County: GRAHAM	Fraction 1/4 SW 1/4 SW 1/4 N E 1/4	Section Number Township No. Range Number 30 T 7 S R 23 DE W	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here . Latitude:			
4 Trilles West and 5 Trilles Worth of Tilli Oity		Longitude:	
2 WATER WELL OWNER: ANDY	ANDERSON	Collection Method:	
	OX 100	GPS unit (Make/Model:)	
	CITY KS 67642	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40 ft.			
WITH AN "X" IN SECTION BOX: Depth(s) Grou	ndwater Encountered (1) 30	ft (2) ft (3) ft	
N WELL'S STA	00 1		
Pun	Pump test data: Well water wasft. after hours pumping gpm		
EST. YIELD.	8gpm. Well water was	ft. after hours pumping gpm	
W E Bore Hole Diameter IVin. to .4Vft., andin. toft.			
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well			
SWSE			
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well			
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No			
S If yes, mo/day/yr sample was submitted			
water wen distincted: 105 kg 140			
5 TYPE OF CASING USED: Steel V PVC Other			
CASING JOINTS: Glued Clamped Welded Threaded			
Casing diameter .5 in. to .40 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft., Casing height above land surface. 18 in., Weight .160			
TYPE OF SCREEN OR PERFORATION		IDS./II., Wall thickness or gauge No	
Steel Stainless Steel		Other (Specify)	
	None used (open hole)	Touci (Specify)	
SCREEN OR PERFORATION OPENINGS ARE:			
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)			
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)			
SCREEN-PERFORATED INTERVALS: From40			
From			
From			
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other			
Grout Intervals: From .30 ft.	to .0 ft., From	ft. to ft., From ft. toft.	
What is the nearest source of possible cor	tamination:	,	
	lines Pit privy Livestock		
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well			
Direction from well		torage	
FROM TO LITHOLO		TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0 10 SURFACE CLAY	110111	Diffic. 200 (cone.) of 1 20 Conto in the conto	
10 40 FINE SAND			
T CONTROL CONTROL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged			
under my jurisdiction and was completed on (mo/day/year) .07:19:10 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No444 This Water Well Record was completed on (mo/day/year) .07-19-10			
under the business name of ANDY ANDERSON DRILLING by (signature)			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies			
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.			
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.			
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy			