

LOCATION OF WATER WELL:	Fraction NW ¼ SW ¼ SW ¼	Section Number 24	Township Number T 7 S	Range Number R 27 W EW
-------------------------	----------------------------	----------------------	--------------------------	---------------------------

Distance and direction from nearest town or city street address of well if located within city?

N/A - LOCATION CONFIRMED BY GMD #4

WATER WELL OWNER: Larry Cressler RR#, St. Address, Box # : Rt 1 Box 26 City, State, ZIP Code : Hoxie, KS 67740	Board of Agriculture, Division of Water Resources Application Number:
--	--

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL: 24' ft. ELEVATION:	Board of Agriculture, Division of Water Resources Application Number:
	Depth(s) Groundwater Encountered 1. DRY ft. 2. ft. 3. ft.	
	WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr	
	Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm	
	Bore Hole Diameter in. to ft., and in. to ft.	
	WELL WATER TO BE USED AS: X1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was sub-mitted		Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED: X1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass	CASING JOINTS: Glued Clamped Welded Threaded
Blank casing diameter 6 in. to ft., Dia in. to ft., Dia in. to ft.	Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.		
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.		

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	Grout Intervals: From 6 ft. to 2 ft., From ft. to ft., From ft. to ft.	What is the nearest source of possible contamination: NONE 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		ENTER			BOTTOM TO 6' - DIRT
					6' - 2' BENTONITE
		PLUGGING			2 0 CLAY
		INFORMATION			
		AT			
		RIGHT			

RECEIVED

NOV 30 1989

DIVISION OF ENVIRONMENT

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-15-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 11-15-89 under the business name of by signature Larry Cressler
--