USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## REXTORN NE

## WATER WELL RECORD KSA 82a-1201-1215

ANC

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County	Fraction		Section number		Township number	Range number		
	Sheridan	SW <sub>1/4</sub> SE <sub>1/4</sub> NE	1/4	11	_	T 7 s	<sub>R</sub> 29	€/W	
2. Distance and direction from nearest town or city: Hoxie, Kansas  3. Owner of well: Phillip Sealock									
4½ ml. West; / ml. North   Street address of well location if in city:					R. or street: ity, state, zip code: Hoxie, Kansas 67740				
4. Locate with "X" in section below: Sketch map:					6. Bore hole dia. 30 in. Completion date				
N						Well depth 255 ft.	11-16-78	}	
						7Cable toolRotaryDrivenDugHollow rodJettedBored X Reverse rotary			
E - SW SE I I I I I I I I I I I I I I I I I					ŀ	8. Use: Domestic Public supply Industry			
						X Irrigation Air conditioning Stock			
					LawnOil field waterOther 9. Casing: Material Steel Height: Above or below				
						Threaded Welded X Surface 12 in.			
S						RMPPVCWeight 31.75_lbs./ft. Dia 16_in. to 255 ft. depth Wall Thickness: inches or			
5. Type and color of material				From	То	Dia LQ in. to LQ ft. de	oth gage No18	38	
7,7						10. Screen: Manufacturer's			
Clay				0	45		d <sub>Dig.</sub> 16		
Sand & Gravel Clay Streaks				45	108	Slot/gauze 100 Set between 245	Length10	White State	
				1.5	1.00	Set between 245 Perf Brown 185.	_ft. and	manuscript ft.	
Clay & Sand Streaks				108	130	Gravel pack? X Size ro	AND DESCRIPTION OF THE OWNER OWN	dipro-manufacture (manufacture)	
Sand & Gravel				130	133	11. Static water level:  140 ft. below land su		o./day/yr. 21-78	
Clay, Sand & Gravel Streaks				133	1 1	$2^{12}_{45}$ Pumping level below land		water and the same of the same	
Coarse Sand & Gravel				140	150	ft. after	hrs. pumping	g.p.m.	
Clay, Sand & Gravel Streaks				150	164	Estimated maximum yield		g.p.m.	
						Yes <u>X</u> No Date			
Sandstone, Sand Mix & Sand				164	185	Distance advantage 12			
Coarse Sand & Gravel				185	190	15. Well grouted? Yes			
Clay				190	208	With: Neat cement Depth: From 0 ft. to	Bentonite X	Concrete	
Cogrego Cond C Curred				000	007	16. Nearest source of possib		MARKON MARKANIA MARKA	
Coarse Sand & Gravel				208	227	ft. 2600 Direction	North Type Fa		
Ochre				227	232	Well disinfected upon compl 17. Pump:	Not installed		
Coarse Sand & Gravel				232	253	Manufacturer's name <u>F1</u>	oway	~_	
Ochre & Shale				253	260	Model number 12 DOL Length of drop pipe 251	HP <u>100</u> Vo ft. capacity <u>80</u>		
BROCK 771'						Type:			
12000					(COMMON ASSAULTANIA (COMMON ASSAULTANIA (COMMON ASSAULTANIA (COMMON ASSAULTANIA (COMMON ASSAULTANIA (COMMON AS	Submersible Jet	<u>X</u> Turbir Recip	ne rocating	
(Use a second sheet if needed)						Centrifugal	Other	1 1 1	
18. Elevation: 19. Remarks:					20. Water well contractor's certification: This well was drilled under my jurisdiction and this report				
[ Tanamahu						is true to the best of my knowledge and belief.			
Topography:  Hill						Western Well & Pump, Inc. 245 Business name License No.			
Slope						Address Box 852 Colby, KS 67701			
X Upland Valley						Signed Authorized representative Date			