

J.L.

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

BCD

1. Location of well:		County Sheridan	Fraction SE 1/4 SW 1/4 SE 1/4	Section number 12	Township number T 7 S R 29	Range number 29	X W																																																				
2. Distance and direction from nearest town or city: Hoxie, KS 6 1/2 mi. North; 3 1/4 mi. West Street address of well location if in city:				3. Owner of well: Dave Schamberger R.R. or street: City, state, zip code: Hoxie, Kansas 67740																																																							
4. Locate with "X" in section below: Sketch map: N W E S 1 Mile 1 Mile				6. Bore hole dia. 30 in. Completion date _____ Well depth 252 ft. 1-10-79																																																							
<table border="1"> <tr> <td colspan="2">5. Type and color of material</td> <td>From</td> <td>To</td> </tr> <tr> <td colspan="2">top Soil</td> <td>0</td> <td>160</td> </tr> <tr> <td colspan="2">fine sand</td> <td>160</td> <td>165</td> </tr> <tr> <td colspan="2">sand stone</td> <td>165</td> <td>180</td> </tr> <tr> <td colspan="2">fine sand sandstone</td> <td>180</td> <td>196</td> </tr> <tr> <td colspan="2">fine sand medium gravel</td> <td>196</td> <td>206</td> </tr> <tr> <td colspan="2">sandstone & clay</td> <td>206</td> <td>215</td> </tr> <tr> <td colspan="2">fine sand medium gravel</td> <td>215</td> <td>220</td> </tr> <tr> <td colspan="2">fine sand medium gravel st. clay & sandstone</td> <td>220</td> <td>230</td> </tr> <tr> <td colspan="2">fine sand medium gravel st. clay sandstone</td> <td>230</td> <td>240</td> </tr> <tr> <td colspan="2">fine sand medium gravel</td> <td>240</td> <td>247</td> </tr> <tr> <td colspan="2">ochre & shale</td> <td>247</td> <td>260</td> </tr> <tr> <td colspan="2" style="text-align: center;">(Use a second sheet if needed)</td> <td></td> <td></td> </tr> </table>				5. Type and color of material		From	To	top Soil		0	160	fine sand		160	165	sand stone		165	180	fine sand sandstone		180	196	fine sand medium gravel		196	206	sandstone & clay		206	215	fine sand medium gravel		215	220	fine sand medium gravel st. clay & sandstone		220	230	fine sand medium gravel st. clay sandstone		230	240	fine sand medium gravel		240	247	ochre & shale		247	260	(Use a second sheet if needed)				7. Cable tool <input type="checkbox"/> Rotary <input checked="" type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
				5. Type and color of material		From	To																																																				
top Soil		0	160																																																								
fine sand		160	165																																																								
sand stone		165	180																																																								
fine sand sandstone		180	196																																																								
fine sand medium gravel		196	206																																																								
sandstone & clay		206	215																																																								
fine sand medium gravel		215	220																																																								
fine sand medium gravel st. clay & sandstone		220	230																																																								
fine sand medium gravel st. clay sandstone		230	240																																																								
fine sand medium gravel		240	247																																																								
ochre & shale		247	260																																																								
(Use a second sheet if needed)																																																											
				8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																																																							
				9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 34.85 lbs./ft. Dia. 16 in. to 252 ft. depth Wall Thickness: inches or Dia. _____ in. to _____ ft. depth gage No. 204																																																							
				10. Screen: Manufacturer's name Cook Type Wire Wrapped Dia. 16 Slot/gauze 100 Length 10 Set between 242 ft. and 252 ft. Brown Perf 182 and 242 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 30% #1-70 1/4x5																																																							
				11. Static water level: _____ mo./day/yr. 147 ft. below land surface Date 1-12-79																																																							
				12. Pumping level below land surfaces: 186 ft. after 1 hrs. pumping 825 g.p.m. 177 ft. after 1 hrs. pumping 556 g.p.m. Estimated maximum yield 1100 g.p.m.																																																							
				13. Water sample submitted: _____ mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date _____																																																							
				14. Well head completion: <input type="checkbox"/> Pitless adapter 12 Inches above grade																																																							
				15. Well grouted? <input checked="" type="checkbox"/> YES With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.																																																							
				16. Nearest source of possible contamination: ft. 1200 Direction ESE Type Farm Stead Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																																							
				17. Pump: _____ Not installed Manufacturer's name Floway Model number 10DOH HP 70 Volts - Length of drop pipe 250 ft. capacity 600 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																																							
18. Elevation: Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		19. Remarks: moved from original location in the NE 1/4 of SE 1/4 of 12-7-79		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Western Well & Pump Inc. 245 Business name License No. _____ Address Box 852 Colby, KS. 67701 Signed [Signature] Date 2-31-79 Authorized representative																																																							

T
R
S
1/4
SE
SW
NW
NE

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5