


1 LOCATION OF WATER WELL: County: Clay Fraction: SW 1/4 SW 1/4 SE 1/4 Section Number: 23 Township Number: T 7 S Range Number: R 3 E/W
 Distance and direction from nearest town or city street address of well if located within city? From Gira Co 1/2 mile South on 859 To 21st & Co West 2 1/2 miles

2 WATER WELL OWNER: Harold Alexander
 RR#, St. Address, Box #: 2088 21st St Rd. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Clay Center, KS 67432 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1 60 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 60 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 2.0 gpm. Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) welded
 7 Fiberglass Threaded
 Blank casing diameter: 5 1/4 in. to 100 ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface: 2' in. weight 56 lb 40 lbs./ft. Wall thickness of gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 25/10005 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 100 ft. to 120 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 2.5 ft. to 120 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 5 ft. to 2.5 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines None Close 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			
1	21	Brown Clay			
21	22	Limestone			
22	42	Yellow Shale			
42	51	Limestone			
51	57	Brown Shale			
57	59	Limestone			
59	75	Greenish Shale (Water)			
75	80	Brown Shale			
80	91	Limestone			
91	108	Grey Oily Shale			
108	112	Limestone			
112	120	Grey Oily Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/15/2001 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 4590 This Water Well Record was completed on (mo/day/yr) 1/28/2005 under the business name of Holdman Well Drilling by (signature) Craig H. Curtis