Scenario Substance and direction from nearest town or city street address of well if located within city?
Distance and direction from nearest town or city street address of well if located within city? 2 WATER WELL OWNER: Vernon Vance RR#, St. Address, Box # 310 School St City, State, ZIP Code Rexford, Ks 67753 3 AN "X" IN SECTION BOX: A DEPTH OF COMPLETED WELL Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/daylyr Pump lest data: Well water was ft. after hours pumping gpm Well WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/daylyr sample was Submitted S Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Casing height above land surface 18 in., weight 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 Staliniess steel 5 Fiberglass 8 RMP (SR) 1 Steel 3 Staliniess steel 5 Fiberglass 8 RMP (SR) 1 Steel 3 Staliniess steel 5 Fiberglass 8 RMP (SR) 1 Steel 3 Staliniess steel 5 Fiberglass 5 Gauzed wrapped 9 ABS 12 None used (open hole) 2 Strass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) 3 Staliniess steel 5 Fiberglass 5 Gauzed wrapped 9 Dilled holes 3 Staliniess steel 5 Fiberglass 5 Gauzed wrapped 9 Dilled holes 3 Staliniess steel 5 Fiberglass 5 Gauzed wrapped 9 Dilled holes 3 Staliniess steel 5 Fiberglass 5 Gauzed wrapped 9 Dilled holes 3 Staliniess steel 5 Fiberglass 5 Gauzed wrapped 9 Dilled holes 3 Staliniess steel 5 Fiberglass 5 Gauzed wrapped 9 Dilled holes 3 Staliniess steel 5 Fiberglass 5 Fibe
2 WATER WELL OWNER: Vernon Vance RRR, St. Address, Box #: 310 School St Rexford, Ks 67753 3 LOCATE WELLS LOCATON WITH AN "X" IN SECTION BOX": AN X" IN SECTION BOX": Bepth (s) Groundwater Encountered 1
RR#, St. Address, Box # 310 School St City, State, ZIP Code Rexford, Ks 67753
City, State, ZIP Code Rexford, Ks 67753 Application Number: Control C
City, State, ZIP Code Rexford, Ks 67753 Application Number: Control C
3 COATE WELL'S LOCATON WITH AN X' IN SECTION BOX: Purplest data: Depth (s) Groundwater Encountered 1 ft. 2 ft. 3 ft. 3 ft. 4
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Well Water Na ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Well Water Na ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm In. to Manufacer supply 9 Dewatering 12 Other (Specify below) Water Well Disinfected? Yes X No No In. to Manufaced? Yes X No In. to Manufaced? Yes X No In. to Manufaced? Yes X No No In. to Manufaced? Yes
WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 220 ft. and in. to ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 4.5 in. to 180 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 18 in., weight 2.38 lbs./ft. Walt thickness or gauge No. 248 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) 5 CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 5 SCREEN-PERFORATED INTERVALS: From 180 ft. to 220 ft. From ft. to ft. From ft. to ft.
Pump test data: Well water was ft. after hours pumping gpm gpm Well water was ft. after hours pumping gpm gpm Well water was ft. after hours pumping gpm gpm well water was ft. after hours pumping gpm gpm gpm gpm gpm gpm gpm gpm gpm gp
Est. Yield gpm: Well water was ft. after hours pumping gpm well water was ft. after hours pumping gpm well water was ft. after hours pumping gpm meter s in. to 220 ft. and in. to ft. well water SPD set SED AS: 5 Public water supply 9 Dewatering 11 Injection well well water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted water well Disinfected? Yes X No 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded In. to ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 18 in., weight 2.38 Ibs./ft. Wall thickness or gauge No. 248 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drilled holes 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft. From
Est. Yield gpm: Well water was ft. after hours pumping gpm well water was ft. after hours pumping gpm well water was ft. after hours pumping gpm meter s in. to 220 ft. and in. to ft. well water SPD set SED AS: 5 Public water supply 9 Dewatering 11 Injection well well water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted water well Disinfected? Yes X No 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded In. to ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 18 in., weight 2.38 Ibs./ft. Wall thickness or gauge No. 248 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drilled holes 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft. From
Bore Hole Diameter 8 in. to 220 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 11 Injection well 11 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/daylyr sample was submitted Water Well Disinfected? Yes X No Water Well Disinfected? Yes X No S Type OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/daylyr sample was submitted water Well Disinfected? Yes X No S Type OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded Surface Threaded Surface Threaded Surface 18 in., weight 2.38 Ibs./ft. Walt thickness or gauge No. 248 Type OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement State S
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 4.5 in. to 180 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 18 in., weight 2.38 Ibs./ft. Walf thickness or gauge No. 248 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 180 ft. to 10 Cther ft. From ft. to ft. From ft. to ft. From ft. to ft.
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 4.5 in. to 180 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 18 in., weight 2.38 Ibs./ft. Walf thickness or gauge No. 248 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 180 ft. to 10 Cther ft. From ft. to ft. From ft. to ft. From ft. to ft.
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Submitted Water Well Disinfected? Yes X No Water Well Disinfected? Yes X No S If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No S If yes, mo/day/yr sample was submitted Submitted Submitted to Department? Yes No X If yes, mo/day/yr sample was was submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes X No S If yes, mo/day/yr sample was was submitted to Department? Yes No X If yes, mo/day/yr sample was was submitted to Department? Yes No X If yes, mo/day/yr sample was was submitted to Department? Yes No X If yes, mo/day/yr sample was was submitted to Department? Yes No X If yes, mo/day/yr sample was was submitted to Department? Yes No X If yes, mo/day/yr sample was was submitted to Department? Yes No X If yes, mo/day/yr sample was submitted to Department? Yes No Nation Submitted to Department? Yes X No No Submitted to Pask X Clamped Submitted to Pescify Submitted to Pescify Submitted to Department? Yes X No
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted was submitted to Department? Yes No X If yes, mo/day/yr sample was was submitted was submitted was submitted to Department? Yes No X If yes, mo/day/yr sample was was submitted was submitted to Department? Yes No X If yes, mo/day/yr sample was was was submitted to Department? Yes No X If yes, mo/day/yr sample was was was submitted to Department? Yes No X If yes, mo/day/yr sample was was was submitted to Department? Yes No X If yes, mo/day/yr sample was was was appled to Department? Yes No X If yes, mo/day/yr sample was was was proved in the fill Department? Yes No X If yes, mo/day/yr sample was was wasted Yes X No No No X If yes, mo/day/yr sample was was wasted X Department? Yes No X If yes, mo/day/yr sample was wasted X Department? Yes No X If yes, mo/day/yr sample was wasted X Department? Yes X No No X If yes, mo/day/yr sample was wasted X Department? Yes X No No X If yes, mo/day/yr sample was wasted Yes X No No X If yes, mo/day/yr sample was wasted yes X No No X If yes, mo/day/yr sample was submitted to Department? Yes X No No X If yes, mo/day/yr sample was wasted Yes X No No X If yes, mo/day/yr sample was wasted Yes X No No X If yes, mo/day/yr sample wasted X Department? Yes X No No X If yes, mo/day/yr sample wasted Yes X No No X If yes, mo/day/yr sample wasted Yes X No No X If yes, mo/day/yr sample wasted Yes X No No X If yes, mo/day/yr sample wasted Yes X No No X If yes, mo/day/yr sample wasted Yes X No No X If yes, mo/day/yr sample wasted Yes X No No Yes X No No Yes X No
S
5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 4.5 in. to 180 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 18 in., weight 2.38 lbs./ft. Walf thickness or gauge No. 248 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 180 ft. to 16. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From ft. to ft. From ft. to ft. From ft. to ft.
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 4.5 in. to 180 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 18 in., weight 2.38 lbs./ft. Wall thickness or gauge No248 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 180 ft. to 10 ft. From 11 ft. to ft. From 11 ft. to 11 ft. From 11 ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From 11 ft. to ft. From 11 ft. to ft. From 11 ft. to ft.
2 PVC
Blank casing diameter 4.5 in. to 180 ft., Dia in. to ft., Dia in. to ft. Dia in. to in.
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 180 ft. to 220 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From ft. to ft. From ft. to 15 From ft. from ft. to ft.
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 180 ft. to 220 ft. From ft. to ft. to From ft. to 220 ft. From ft. to ft. to GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From ft. to ft. to From ft. to 20 ft. From ft. to ft.
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 180 ft. to 220 ft. From ft. to ft. to From ft. to 220 ft. From ft. to ft. to GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From ft. to ft. to From ft. to 20 ft. From ft. to ft.
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 180 ft. to 220 ft. From ft. to ft. ft. From ft. to 220 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From ft. to ft. From ft. to ft. from ft. to ft.
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 180 ft. to 220 ft. From ft. to ft. From ft. to ft. from ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From ft. to ft. From ft. to ft. From ft. to ft.
SCREEN-PERFORATED INTERVALS: From 180 ft. to 220 ft. From ft. to ft. From ft. to ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From ft. to ft. From ft. to ft. From ft. from ft. to ft.
From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From ft. to ft. From ft. to ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 20 ft. to 220 ft. From ft. to ft. from ft. to ft.
From ft. to ft. From ft. to ft.
From ft. to ft. From ft. to ft.
6 CROUT MATERIAL: 1 Next coment 2 Coment grout 2 Pontonite 4 Other
GROOT MATERIAL. 1 Neat cement 2 Cement grout 5 Bentonite 4 Other
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage NONE
Direction from well? How many feet?
FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 2 Surface Lenses
2 28 Loess 113 121 Fine to med sd w/clay & caliche strks
28 45 Fine to med sd w/clay & caliche 121 127 Fine to some med sd w/clay & caliche
Strks Lenses
45 51 Caliche w/clay strks 127 136 Fine sd & sdy clay w/clay & cal lenses 51 68 Fine to med sd w/clay & caliche 136 147 Fine to some med sd w/cal lenses
Lenses 147 156 Fine to some med sd w/clay&cal strks
68 80 Clay & caliche w/sd lenses 156 162 Fine &med sd w/clay & caliche strks
80 86 Fine sd & sandy clay w/clay & 162 169 caliche
Caliche 169 184 Fine & med sd w/caliche strks
86 94 Clay & caliche w/sd lenses 184 190 Fine & med sand
94 100 Fine to some med sd w/clay & 190 194 Clay
Caliche strks 194 212 Fine & med sd w/clay lenses
100 113 Fine to some med sd w/clay 212 220 Yellow ochre
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was
· · · · · · · · · · · · · · · · · · ·
completed on (mo/day/yr) 5-15-08 and this record is true to the best of my knowledge and belief. Kansas
completed on (mo/day/yr) 5-15-08 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. Under the business name of Woofter Pump & Well Inc. INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W