1 LOCATION OF WATER W	/ELL: Fraction	Section	n Number	Township Number	Range Number
County: Thoma	SW "SE "SW			T S	R 3/ EW
Distance and direction from ne	earest town or city street address of well if located w	rithin city?	<u> </u>	1 3	, , o
2 WATER WELL OWNER:					
RR#, St. Address, Box # :				Board of Agriculture, D	ivision of Water Resources
City, State, ZIP Code :	Colby, Ks 67701			Application Number:	
3 AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL Depth(s) Groundwater Encountered 1	235	ft. ELE	VATION:	
N	Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL		f	î. 2 fi.	3ft.
1 ×	WELL'S STATIC WATER LEVEL	na ft. b	elow land	surface measured on mo/da	ny/yr
	Pump test data: Well water	was		ft. after hour	s pumping gpm
	Est. Yield gpm: Well water	was		ft. after hour	s pumping gpm
<sup>2</sup> W → ↓	Bore Hole Diameter 8 in. to WELL WATER TO BE USED AS: 5 Pt 1 Domestic 3 Feed lot 6 Oi	240		ft. and	in. to ft.
ī <b>l</b> ! l !	WELL WATER TO BE USED AS: 5 PU	ublic water sup	ply	8 Air conditioning	11 Injection well
SW SE	Domestic 3 Feed lot 6 Of	i field water st	abbià	9 Dewatering	12 Other (Specify below)
	2 Irrigation 4 Industrial 7 La				
S	Was a chemical/bacteriological sample s	ubmitted to De			i
<del></del>	submitted	0.0		ater Well Disinfected? Yes	
5 TYPE OF BLANK CASING	_				ued X Clamped
	3 RMP (SR) 6 Asbestos-Cement		-	ow) We	elded
teres.	4 ABS 7 Fiberglass			Th	readed
Biank casing diameter	4.5 in. to 195 ft., Dia	in. to		ft., Dia	in. to ft.
Casing height above land surf	face 18 in., weight FORATION MATERIAL:	2.38	ibs./ft.	Wall thickness or gauge N	o248
	3 Stainless steel 5 Fiberglass	٢	VC	10 Aspestos-cei	nent
	4 Galvanized steel 6 Concrete tile	9 4	RS (SR)	12 None used (c	y)
SCREEN OR PERFORATION	OPENINGS ARE: 5 Gauze	ed wrapped		8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot 6 Wire v	vrapped		9 Drilled holes	(3,000,000)
2 Louvered shutter	4 Key punched 7 Torch	cut		10 Other (specify)	
SCREEN-PERFORATED INT	ERVALS: From 195 ft. to	235	ft.	From f	t. to ft.
	From ft. to		ft.	From f	t. to ft.
GRAVEL PACK INTE		235	ft.	From f	t. to ft.
	From ft. to		ft.	From f	t. to ft.
6 GROUT MATERIAL:	1 Neat cement 2 Cement grout	3 Bento	nite	4 Other	
Grout Intervals From	0 ft. to 20 ft. From	ft. to		ft. From	ft. toft.
What is the nearest source of	possible contamination:		10 Live	stock pens 14 /	
1 Septic tank	4 Lateral lines 7 Pit privy				Oil well/ Gas well
2 Sewer lines	5 Cess pool 8 Sewage			•	Other (specify below)
	es 6 Seepage pit 9 Feedyard				none
Direction from well?	DDE LITUOLOGIC LOC		How man	<u> </u>	INITEDVALS
FROM TO CO	DDE LITHOLOGIC LOG Surface	140	160	Fine sand & calich	INTERVALS
2 24	Loess	160		Fine sand, clay & c	
24 60	Clay	167	180	Fine to med sd, cla	y & caliche lenses
60 72	Fine to med sand & gravel	180	181	Caliche, hard	
72 75	Clay	181		Med to coarse san	d
75 83	Fine to some med sand	183		Clay	
83 88	Sandstone & fine sand	184		Fine to med sd, cla	
88 108	Fine sand w/clay lens	194		Clay & caliche & fi	
108 117 117 126	Fine to med sand & gravel Fine sand w/clay lens	198	224	Med to coarse sd, Lenses	Source Atanat cist
126 135	Fine to some med sd w/clay &	224	225	Clay	
120 100	Caliche	225		Med sand	
135 138	Med sand	228		Clay	
138 140	Clay & caliche	232		ochre	
7 CONTRACTOR'S OR LAN	NDOWNER'S CERTIFICATION: This water well was	(1) constructe	d, (2) reco	nstructed, or (3) plugged un	
completed on (mo/day/yr)	7-19-06	and this	record is	true to the best of my knowl	edge and belief. Kansas
Water Well Contractor's Licen	se No. 554	This Wa	iter Well R	ecord was completed on (n	no/day/yr) 7-21-06
under the business name of	Woofter Pump & Well I	nc.	1	ov (signature)	
INSTRUCTIONS: Please	fill in blanks and circle the correct answers. Send three of	copies to Kansas	s Departme	nt of Health and Environment,	Bureau of Water, 1000 S W
Jackson St., Sta. 420, Tob	eka, Kansas 66612-1367, Telephone: 913-296-5545, Se	end one to WAI	IEK WELL	Uvvnek and retain one for vo	ur records.