


1 LOCATION OF WATER WELL: Fraction NE 1/4 Section Number 3 Township Number T 7 S Range Number R 21 E
 County: Thomas
 Distance and direction from nearest town or city street address of well if located within city?
1/2 N W Rexford KS.

2 WATER WELL OWNER: Fred Aibers
 RR#, St. Address, Box #: Rexford KS.
 City, State, ZIP Code: Rexford KS.
 Board of Agriculture, Division of Water Resources
 Application Number: 36224

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 217.5 ft. ELEVATION: 122 ft.
 Depth(s) Groundwater Encountered 1. 122 ft. 2. 122 ft. 3. 122 ft.
 WELL'S STATIC WATER LEVEL 122 ft. below land surface measured on mo/day/yr 11/15/82
 Pump test data: Well water was 950 gpm. Well water was 20 ft. after 132 1/2 hours pumping 11/15/82 gpm
 Est. Yield 950 gpm: Well water was 20 ft. after 132 1/2 hours pumping 11/15/82 gpm
 Bore Hole Diameter 20 in. to 232 1/2 ft., and 232 1/2 in. to 232 1/2 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel ✓ 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ✓ Clamped ✓
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ✓
 7 Fiberglass Threaded.
 Blank casing diameter 12 in. to 217.5 ft. Dia. 12 in. to 217.5 ft. Dia. 12 in. to 217.5 ft. Dia. 12 in. to 217.5 ft. Dia.
 Casing height above land surface 12 in., weight 1.88 lbs./ft. Wall thickness or gauge No. 1.88
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 12
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter ✓ 4 Key punched 6 Wire wrapped 9 Drilled holes 12 None (open hole)
 7 Torch cut 10 Other (specify) 12
 SCREEN-PERFORATED INTERVALS: From 122 1/2 ft. to 232 1/2 ft. From 122 1/2 ft. to 232 1/2 ft. From 122 1/2 ft. to 232 1/2 ft. From 122 1/2 ft. to 232 1/2 ft.
 GRAVEL PACK INTERVALS: From 10 ft. to 232 1/2 ft. From 10 ft. to 232 1/2 ft. From 10 ft. to 232 1/2 ft. From 10 ft. to 232 1/2 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 232 1/2 ft. From 10 ft. to 232 1/2 ft. From 10 ft. to 232 1/2 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) None
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	115	0146 S d clay - ss			
115	135	35 M Gravel - S clay			
135	145	04 S clay			
145	155	23 Sand Stone			
155	175	M Gravel			
175	195	14			
195	205	07 F Sand			
205	225	M Gravel - sandy clay			
225	232 1/2	35			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-7-83 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 214 This Water Well Record was completed on (mo/day/yr) 6-22-83
 under the business name of Blue Jay Drilling Inc by (signature) John Hall
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4

D