


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

66111E

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Thomas	Township name Smith	Fraction SW-SE$\frac{1}{4}$	Section number 17	Town number 7	Range number 31
Distance and direction from nearest town or city: 2 miles SW of Street address of well location if in city: Rexford, Ks.				3 Owner of well: Baalman & Sons Address: Hoxie, Kansas		
Locate with "X" in section below: 				4 Well depth: 220 ft. Date of completion 1-23-75 Well diameter 28 in.		
2 Type and color of material				5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well <input type="checkbox"/>		
From To				7 Casing: Material steel Weight: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. 16 in. to 150 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
				8 Screen: Manufacturer W. A. Brown Type bridge Dia. 16" Slot/gauze 1/8 Length 2' Set between 150 ft. and 210 ft. Fittings: 10' of cook - 210 - 220 Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material x 5/8		
Clay & sand streaks				9 Static water level: 120 ft. below land surface Date 1-25-75		
				10 Pumping level below land surfaces: 190 ft. after 2 hrs. pumping 1500 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 1500 g.p.m.		
Sandy clay & fine to coarse sand & gravel				11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date		
				12 Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade		
Fine to coarse sand & gravel & few clay lenses				13 Well grouted? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite & clay Depth: From 0 ft. to 10 ft.		
				14 Nearest source of possible contamination: ft. 1 mile Direction NW Type unknown Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Fine to coarse sand & gravel & loose				15 Pump: Manufacturer's name Byron Jackson Not installed Model number 210 HP 150 Volts Length of drop pipe 210 ft. capacity 1500 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
				16 Remarks: elevation 3009 (TOP) 3008		
Shale				17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Western Well & Pump Inc. 245 Business name License No. Address P.O. Box 852, Colby, Ks. Signed Roy F. Jackson Date Aug 28-75 Authorized representative		
				16 Remarks: elevation 3009 (TOP) 3008		