USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

South Well

	County	Fraction		Section	number	Township number	Range number		
1. Location of well:	Thomas	SW 1/4 SW 1/4 SE	1/4	31		т 7 ѕ	r 32	X≛/W	
COIDY				er of well: H & H Farms					
5½ Miles Easet; 500' North Street address of well location if in city: City sta				street: P.O. Box 564 ste, zip code: Colby, KS 67701					
4. Locate with "X" in section below: Sketch map:					6. Bore hole dia. 32 in. Completion date				
N State Hilliam						Well depth <u>256</u> ft. <u>9–12–78</u>			
□						7Cable toolRotaryDrivenDug			
					-	Bored X Reverse rotary 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material Steel Height: Above or below Threaded Welded X Surface 12 in.			
to breatanananananananananananananananananana						RMPPVCWeight_31.75_lbs./ft.			
5. Type and color of material				From	То	Dia. 16 in. to 25.6ft. depth Wall Thickness: inches or Diain. toft. depth gage No1.88			
3. Type and color of indicator				1,011		10. Screen: Manufacturer's n	ame		
Clay				0	60	Cook Type Wire Wrappe		6	
Sand & Gravel & Clay				60	61	Slot/gauze50	Length20		
				00	0.1	Set between236ft. and256ft. Perf-Brown 176and236ft.			
Clay				61	80	Gravel pack? Size ra			
Sand & Clay				80	90	11. Static water level: 127 ft. below land sur		mo./day/yr. #1	
				00	100	12. Pumping level below land		head and the latest th	
Coarse Sand & Gravel					109	174 ft. after1	nrs. pumping 208		
Fine Med. Sand & Clay Streaks				109	129	ft. after hrs. pumping g.p.m. Estimated maximum yield 3000 g.p.m.			
Med. Coarse Sand & Gravel				129	138	13. Water sample submitted:	r	mo./day/yr.	
Clay				138	145	Yes X No Date 14. Well head completion:			
						Pitless adapter			
Med. Coarse Sand				145		15. Well grouted? <u>yes</u> With: <u>X</u> Neat cement	Pantanita	Congrete	
Clay Sand & Cement Streaks				ļ	191	Depth: From ft. to	ft.	Concrete	
Coarse Sand & Gravel				191	254	16. Nearest source of possible contamination:			
Ochre & Shale				254	260	ft. 2600 Direction West Type Farmstead Well disinfected upon completion? Yes X No			
ochre a share				1 4 5 4	200	17. Pump:	Not installe	-X-No W	
Na and the same an			TO MANAGE HE WAS ASSESSED TO BE ASSESSED TO BE ASSESSED TO BE ASSESSED.	-		Manufacturer's name	Floway _ HP 130	Volts	
						Length of drop pipe 197		20 0.p.m. (≦)	
						Type: Submersible	X_ Turk	oine	
						Jet		iprocating of U	
(Use a second sheet if needed)CentrifugalOther of contractor's certification:								er	
DD-01/ 7/16					This well was drilled under my jurisdiction and this report				
Topography:							c 245 \$M		
—Hill					Business name License No.			License No.	
X Upland						Address Box 852	Colby, KS Serr	S 67701 S S	
Valley Signed 1 Control Date 10 of 1								N 2 4 ASSAULT OF THE	
							_	21	