USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

NORTH WELL

	County		İ	Section number		Township number	Range number		
1. Location of well:	Thomas	NW 1/4 NW 1/4 NE 1/4				r 7	s R 32	XE/W	
, COIDY				er of well	ı: H	& H Farms	itatuulusuus elektrimisessa kastaasia eessa kastaasia ja m	**************************************	
Street address of well location if in city.				street:		2.0. Box 564			
City, st					state, zip code: Colby, KS 67701				
4. Locate with "X" in section below:  N						6. Bore hole dia. <u>32</u> i Well depth <u>260</u> ft.			
X   X						7Cable toolRotaryDrivenDugHollow rodJettedBored X_Reverse rotary			
E - SW SE						8. Use: Domestic Public supply Industry  X			
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					1	9. Casing: Material Steel Height: Above or below Threaded Welded X Surface 12 in.			
S I Mile					1	RMPPVC	Weight_3I	$325$ _lbs./ft.	
5. Type and color of material						Dia. 16 in. to 260ft. depth Wall Thickness: inches or Diain. toft. depth gage No. 188			
Clay					60	10. Screen: Manufacturer's  Cook			
				0	60	TypeWire Wrapped Dia. 16 Slot/gauze 50 Length 20'			
Coarse Sand & Gravel Clay				92	92 120 <sup>I</sup>	Set between <u>240</u> ft. and <u>260</u> ft. Perf-Brown 180 and <u>240</u> ft.			
-					120	Gravel pack? $X$ Size range of materia $70\%$ $\frac{1}{4}X5/8$			
Coarse Sand & Gravel				120 134	134 143	11. Static water level: mo./day/yr.			
Med. Sand				143	$\frac{143}{154}$	131 ft. below land s  12. Pumping level below la	CONTRACTOR OF THE PROPERTY OF THE PARTY OF T	-21-78	
Med. Coarse Sand & Clay Streaks				154	160	183 ft. after 2 hrs. pumping 2276 g.p.m. ft. after hrs. pumping g.p.m.			
Coarse Sand				160	169	Estimated maximum yield 3,000 g.p.m.  13. Water sample submitted: mo./day/yr.			
Clay				169	180	Yes X No Date			
Clay, Sand & Sandstone Mix				***************************************		14. Well head completion: Pitless adapter Inches above grade			
				180	198	15. Well grouted?			
Coarse Sand & Gravel Clay & Sandstone				198 206	206 208 -	Depth: From 0 ft. to 10 ft.			
						16. Nearest source of possil ft. 5100 Direction	ole contamination: SW Type	Earmstea	d '
Coarse Sand & Gravel			CONTRACTOR OF THE PROPERTY OF	208	253	Well disinfected upon comp	oletion?Ye	esNo	
Clay			~**********************	253	256	17. Pump:  Manufacturer's name Floway  Model number 12 DOH Hp 140 Volts			
Coarse Sand & Gravel				256	259	Model number 12 DOH HP 140 Volts Length of drop pipe 197 ft. capacity 1200, p.m.			
Ochre & Shale				259	270	Type: Submersible	<u>"</u> — Ti	urbine	
	(Use a second sl	pact if packed)				Jet Centrifugal		eciprocating Other	~ N
18. Elevation:	19. Remarks:	reer in needed/	BANK MINISTER STREET,		<u> </u>	20. Water well contractor's	The summer of sector and sector a	, ILIGI	ľľ
BRIVE V 759						This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Topography:						Western Well			2 2
Slope						Address Address Address Box 852	Colby, I	KS 67701	2 2
Valley						Signed Authorized re	epresentative	Date 10/2/1	18 8
	The second secon		~				Name and Agents and Ag		, ,