


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Thomas</u>	<u>NE 1/4 SW 1/4 SE 1/4</u>	<u>31</u>	<u>T 7 S</u>	<u>R 33</u> <u>W</u>

Distance and direction from nearest town or city street address of well if located within city?

410 E. 4th

2 WATER WELL OWNER:	DPRA B-10	
RR#, St. Address, Box # :	<u>Colby Locker-Easement of City of Colby</u>	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	<u>410 E. 4th, Colby, Ks. 67701</u>	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>125</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>103.3</u> ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter <u>8</u> in. to <u>125</u> ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u> If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No <u>X</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued .. <u>Z</u> .. Clamped ..	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded ..
2 PVC	4 ABS	7 Fiberglass		Threaded. <u>X</u>
Blank casing diameter .. <u>4</u> in. to <u>95</u> ft., Dia ..				
Casing height above land surface .. in., weight .. <u>2.071</u> lbs./ft. Wall thickness or gauge No. <u>237</u>				
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify) ..
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 <u>Saw cut</u>	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) ..	
SCREEN-PERFORATED INTERVALS: From .. <u>95</u> ft. to <u>125</u> ft., From .. ft. to .. ft.				
GRAVEL PACK INTERVALS: From .. <u>93</u> ft. to <u>125</u> ft., From .. ft. to .. ft.				

6 GROUT MATERIAL:	1 Neat cement	<u>2</u> Cement grout	<u>5</u> Bentonite	4 Other	
Grout Intervals: From .. <u>0</u> ft. to .. ft., From .. <u>81</u> ft. to .. <u>93</u> ft., From .. ft. to .. ft.					
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>North</u>				13 Insecticide storage	
				How many feet? <u>200</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	Asphalt	99	103	Fine Silty Sand
6"	4'	Surface	103	107	Med. Sand & Gravel
4'	38'	Sandy silty Brown Clay	107	109	Caliche
38	40	Caliche	109	112	Sand Strks. w/clay
40	46	Clay & Fine Sand Strks.	112	113	Caliche
46	48	Caliche	113	124	Med. Sand
48	50	Fine Sand	124	125	Clay
50	58	Clay, Sand & Caliche Strks.			
58	73	Med. & Fine Sand			
73	75	Caliche			
75	80	Sandy Clay & Caliche Strks.			
80	89	Med. Sand-Clay Layers			
89	92	Hard Cemented Sand			
92	96	Clay & Cemented Strks.			
96	99	Clay & Caliche Strks.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) .. <u>12-2-92</u> .. and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>554</u> .. This Water Well Record was completed on (mo/day/yr) .. <u>2-5-92</u> .. under the business name of <u>Woofter Pump & Well, Inc.</u> by (signature) <u>James C. Woofter</u>
--