	WATER	WELL RECORD	Form WWC-5	KSA 82a		
LOCATION OF WATER WELL:	Fraction	e. 1		ction Number		Range Number
County: 710mas		5W1/4 1	W 1/4	35	T 7 (s)	R 34 E(W)
Distance and direction from nearest to	A * 1 A.	<i>t</i> 1	within city?			
	est of C	ory				
WATER WELL OWNER:	uss Sch	lolder"				
RR#, St. Address, Box # :	2955 CR	.2.2				e, Division of Water Resources
			l		Application Number	
LOCATE WELL'S LOCATION WITH	14 DEPTH OF CO	MPLETED WELL		5. ft. ELEVA	TION:	
AN "X" IN SECTION BOX:	Depth(s) Groundw	ater Encountered 1.		<i>I.06</i> ft. 2	2 ft.	3
1	WELL'S STATIC V	WATER LEVEL		elow land sur	face measured on mo/day/	yr
NW NE	Pump	test data: Well wate	r was	ft. a	fter hours	pumping gpm
						pumping gpm
<u> </u>	Bore Hole Diamete	er		1.75.ft., i	and	in. toft.
* W 1 1 E	WELL WATER TO				8 Air conditioning 1	
-	1 Domestic	3 Feedlot	6 Oil field wa	iter supply	9 Dewatering 1	2 Other (Specify below)
sw st	2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well,	
1 1 1 1 1	Was a chemical/ba	acteriological sample s	ubmitted to D	epartment? Ye	esNoX;الإيلا	es, mo/day/yr sample was sub
S	mitted			Wa	ter Well Disinfected? (Yes	No
TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concr	ete tile	CASING JOINTS: GIL	ued Clamped
1 Steel 3 RMP (\$	SR)	6 Asbestos-Cement	9 Other	(specify below	v) We	elded
2 PVC 4 ABS		7 Fiberglass				readed
Blank casing diameter 55	i .in. to	55ft., Dia	in. to		ft., Dia	in. to برين بير
Casing height above land surface	/.2.i	n., weight		\sim $/90$ lbs./	ft. Wall thickness or gauge	No. 204 40
TYPE OF SCREEN OR PERFORATION			(7 PV	(C)	10 Asbestos-cei	
1 Steel 3 Stainle	ss steel	5 Fiberglass	8 RM	MP (SR)	11 Other (speci-	fy)
2 Brass 4 Galvan	ized steel	6 Concrete tile	9 AE		12 None used (open hole)
SCREEN OR PERFORATION OPENI	NGS ARE:	5 Gauze	ed wrapped		8 Saw cut	11 None (open hole)
1 Continuous slot 3	Mill slot	6 Wire v	vrapped		9 Drilled holes	
2 Louvered shutter 4	Key punched	7 Torch	cut	nc	10 Other (specify)	
SCREEN-PERFORATED INTERVALS						
8-12 Silica San	From	ft. to		ft., From	m	. toft.
GRAVEL PACK INTERVALS	S: From	/.C.C. ft. to		∠.フft., Froi	m ft	. toft.
Returns	From	2 Oft. to			m ft	. to ft.
		Cement grout				
Grout Intervals: From	⊋ft. to ಎೆ	tt., From	ft.	to	ft., From	ft. to ft.
What is the nearest source of possible					tock pens 14	Abandoned water well
1 Septic tank 4 Late	eral lines	7 Pit privy		11 Fuel	storage 15	Oil well/Gas well
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)		
3 Watertight sewer lines 6 See	page pit,	9 Feedyard		13 Insec	ticide storage	
Direction from well? None C	u View			How ma		
FROM TO	LITHOLOGIC L	OG	FROM	то	PLUGGING	INTERVALS
0 100 Ca				ļ		
100 120 clay	7					
	y Sand	tone		<u> </u>		
	ditone			ļ		
160 175 Sand	Stone 4.5	sand	_			
175 Sha	le					
				<u> </u>		
7 CONTRACTOR'S OR LANDOWN	FR'S CERTIFICATIO	N. This water well w	as (1) constru	icted (2) reco	enstructed or (3) plugged in	inder my jurisdiction and was
completed on (mo/day/year)	5-4-97	This water well we	20,000			knowledge and belief. Kansas
Water Well Contractor's License No.	484	This Water W	ell Record w		on (mo/day/yr)	/// // // // // // // // // // // // //
under the business name of	book Dilli	N'	on record Wi	by (signa	///////////////////////////////////////	Keral
	1900		ann fill in his-i			an apping to Vennes Density
INSTRUCTIONS: Use typewriter or ball point of Health and Environment, Bureau of Water	er, Topeka, Kansas 66620-	0001. Telephone: 913-296-5	ase iii in blanks, 545. Send one to	WATER WELL O	WHER and retain one for your reco	ee copies to Kansas Department ords.