USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## South East Well

WATER WELL RECORD KSA 82a-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

900 ya mini da di Cabacco di Ali Cabacci di Const. Cabacci (Cabacci (Cabacc	County	Fraction		Section number		Township number	Range number		
1. Location of well:	Thomas	NE 1/4 NE 1/4 SE	1/4	2		т 7 ѕ	r 34 x€/w	/W	
4 North; 2 West; 1 North; 1 East; ½ North					er of well: Cooper, Willard				
					te, zip code: Colby, Kansas				
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 30 in.	Completion date 7–16-	-76	
N						Well depth 98 ft.			
© W						7Cable toolRotaryDrivenDugHollow rodJettedBored X_Reverse rotary  8. Use:DomesticPublic supplyIndustry		у	
						X Irrigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material Steel Height: Above ox See X			
						Threaded Welded X iSurface 12 in .  RMP PVC Weight188lbs ./ft .			
\$ 11 Mile						Dia. 16 in. to 28 ft. depth Wall Thickness; inches or			
5. Type and color of material				From	То	Diain. toft. dep			
						10. Screen: Manufacturer's r Brown		_	
Top Soil				0	15	Type <u>REgular</u> Slot/gauze 10%	Dia. 16''	-	
Coarse Sand & Gravel				15	26	Set between 28	ft, and 88 ft		
Clay				26	31	10 Cook 88 ft. c	and $\frac{98}{1000}$ finge of material $\frac{1}{200}$	30% #1	
				7.1	<b>(</b> E	11. Static water level:	mo./day/yr		
Coarse Sand & Gravel Layers of Clay				31	65	**************************************	face Date 7-17-76		
Med. Coarse Sand & Gravel Clay & Sand Stone				65	75	12. Pumping level below land			
Clay				75	77	<u>96</u> ft. after <u>2</u> 1	hrs. pumping <u>708</u> g.p.m 708		
Med. Coarse SAnd & Gravel White				77	91	Estimated maximum yield 13. Water sample submitted:	g.p.m mo./day/yi	THE REAL PROPERTY.	
						·	Date	DANIS OF THE STREET	
Clay				91	98	14. Well head completion: Pitless adapter	12 Inches above grade		
Cemented				98		15. Well grouted? X	Clay		
	R	200K (				With:Neat cement	Bentonite X Compared		
	aran raman manan man	Southern Committee and Committ				16. Negrest source of possible	e contamination:		
						ft. 1 M Direction	WNW Type Farm	-	
					ļ	Well disinfected upon comple	etion?YesXN Not installed	7 KW	
						Manufacturer's nameF]	Loway	_ R	
						Model number 056092  Length of drop pipe 90	HP <u>75</u> Volts ft. capacity 550 g.p.m	-	
DESCRIPTION AND CONTRACTOR OF THE PROPERTY OF	rassiniscimics and establishment establishment much in the control of the control					Type: 70 stage 1	XX 10" DOH Bowl		
						Submersible Jet	X Turbine Reciprocating	1	
(Use a second sheet if needed)						Centrifugal	Other	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
18. Elevation:	19. Remarks:					20. Water well contractor's This well was drilled under n	certification: ny jurisdiction and this report	1/2	
					is true to the best of my know	wledge and belief.	_ 1		
Topography:						Western Well &	License No		
Slope						Address Box 852, Co	olby, KS 6770I	3 2 -	
X Upland Valley						Signed Authorized re	presentative Date		
Forward the white, bl	ue and pink copies to the Department	t of Health and Environment				V	V Form WWC-5	# #	