


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

ABD

1. Location of well:	County Thomas	Fraction SE 1/4 NW 1/4 NE 1/4	Section number 28	Township number T 7 S	Range number R 34 E/W
2. Distance and direction from nearest town or city: From Colby; 3 West; 1 3/4 North; 1/4 West Street address of well location if in city:			3. Owner of well: Jeff Melton R.R. or street: City, state, zip code: Colby, Kansas		
4. Locate with "X" in section below: Sketch map: 			6. Bore hole dia. 30 in. Completion date 9-18-76 Well depth 195 ft.		
5. Type and color of material			7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
Clay, Sand, Gravel			8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Sand Stone			9. Casing: Material Steel Height: Above 5 ft. 10 Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 188 lbs./ft. Dia. 16 in. to 125 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. #7		
Clay			10. Screen: Manufacturer's name Brown Type Regular Dia. 16" Slot/gauze 10% Length 60' Set between 125 ft. and 185 ft. 10' Cook 185 ft. and 195 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/2 x 5/8 30% #1		
Coarse Sand, Gravel			11. Static water level: 108 mo./day/yr. 108 ft. below land surface Date 9-20-76		
Clay			12. Pumping level below land surfaces: 192 ft. after 2 hrs. pumping 508 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 520 g.p.m.		
Coarse Sand, Gravel			13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>		
Coa. Sand, Gravel, Cemented Streaks			14. Well head completion: <input type="checkbox"/> Pitless adapter 12 Inches above grade		
Sand Stone, Cemented Sand, Gravel			15. Well grouted? <input checked="" type="checkbox"/> Clay With: <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input checked="" type="checkbox"/> XXXX Concrete <input type="checkbox"/> Depth: From 0 ft. to 10 ft.		
Sand Stone, Rock			16. Nearest source of possible contamination: ft. 7000 Direction SSE Type Farm Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Clay			17. Pump: Manufacturer's name Floway Model number 056183 HP 75 Volts 480 Length of drop pipe 180 ft. capacity <input type="checkbox"/> g.p.m. Type: 10 Stage 10" DOL <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
Coa. Sand, Gravel			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Western Well & Pump 245 Business name License No. Address Box 852, Colby, KS 67701 Signed Dolly Berry Date 10-29-76 Authorized representative		
Ochre, Shale			18. Elevation:		
BROCK 190'			19. Remarks:		
(Use a second sheet if needed)			Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		

1-7 34 28 SE NW NE
1/4 1/4 1/4