

1 LOCATION-OF WATER WELL:		Fraction Near Center ¼ ¼ SE ¼	Section Number 21	Township Number T 7 S	Range Number R 35 EW
Distance and direction from nearest town or city street address of well if located within city? From Colby - 8 Miles West, 2½ Miles North & ½ Mile West.					
2 WATER WELL OWNER: Marge Roulier		RR#, St. Address, Box # : P. O. Box 705			
City, State, ZIP Code : Colby, Kansas 67701		Board of Agriculture, Division of Water Resources Application Number: 19537			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. NA ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 100 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 30 in. to 243 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		(2) Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:					
(1) Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 16 in. to 160 ft., Dia		in. to ft., Dia		CASING JOINTS: Glued Clamped	
Casing height above land surface 12 in., weight 42.05 lbs./ft.		Wall thickness or gauge No. .250		Welded X	
				Threaded.	
TYPE OF SCREEN OR PERFORATION MATERIAL:					
(1) Steel		3 Stainless steel		5 Fiberglass	
2 Brass		(4) Galvanized steel		6 Concrete tile	
				7 PVC	
				8 RMP (SR)	
				10 Asbestos-cement	
				11 Other (specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		(3) Mill slot		5 Gauzed wrapped	
2 Louvered shutter		4 Key punched		(6) Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				11 None (open hole)	
				9 Drilled holes	
				10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 160 ft. to 243 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 243 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement (2) Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				(14) Abandoned water well	
				11 Fuel storage	
				15 Oil well/Gas well	
				12 Fertilizer storage	
				16 Other (specify below)	
				13 Insecticide storage	
Direction from well? WNW				How many feet? 1400	
FROM	TO	LITHOLOGIC LOG		FROM	TO
		See attached log			
		PLUGGING INTERVALS			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-7-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 6-12-89 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.



WESTERN SPRINKLERS, INC.

P. O. BOX 488
1100 South Range
913-462-6755
Colby, Kansas 67701



June 13, 1989

Marge Roulier
320 N. Garfield
Colby, Kansas 67701

Location: Center of SE 1/4 21-7-35, Thomas Co., Kansas
Irrigation Well Log 30".
Static Level 100'
Total Depth 242'

90-105' Gravel & White Clay
105-120' White Clay
120-135' White Clay & Sand
135-150' Sand w/ Clay Layers
150-165' Sand Clay & Sand Stone
165-180' Sandy Clay
180-195' Sand & Clay Layers
195-240- White Fine Sand
240-242' Shale