


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

BREWSTER NE

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Thomas	Township name Barrett	Fraction SE 1/4 of NW 1/4	Section number 16	Town number 7	Range number 36																																																																			
Distance and direction from nearest town or city: About 5 1/2 miles			3 Owner of well: Rex Mayer																																																																						
Street address of well location if in city: North of Brewster, Ks.			Address: Brewster, Kansas																																																																						
Locate with "X" in section below: 			Sketch map:			4 Well depth: 298 ft. Date of completion 1-25-75 Well diameter 28 in.																																																																			
<table border="1"><thead><tr><th>2</th><th>Type and color of material</th><th>From</th><th>To</th></tr></thead><tbody><tr><td></td><td>Clay & sand streaks</td><td>0</td><td>135</td></tr><tr><td></td><td>Fine to coarse sand & cemented</td><td>135</td><td>140</td></tr><tr><td></td><td>Fine to coarse sand</td><td>140</td><td>165</td></tr><tr><td></td><td>Fine sand</td><td>165</td><td>180</td></tr><tr><td></td><td>Fine sand cemented</td><td>180</td><td>181</td></tr><tr><td></td><td>Sandy clay</td><td>181</td><td>194</td></tr><tr><td></td><td>Cemented sand fine</td><td>194</td><td>195</td></tr><tr><td></td><td>Sandy clay fine</td><td>195</td><td>206</td></tr><tr><td></td><td>Fine to coarse sand</td><td>206</td><td>223</td></tr><tr><td></td><td>Cemented sand fine</td><td>223</td><td>238</td></tr><tr><td></td><td>Sandy clay fine</td><td>238</td><td>241</td></tr><tr><td></td><td>Cemented sand fine</td><td>241</td><td>243</td></tr><tr><td></td><td>Fine to coarse sand</td><td>243</td><td>245</td></tr><tr><td></td><td>Cemented</td><td>245</td><td>253</td></tr><tr><td></td><td>Fine to coarse sand & gravel</td><td>253</td><td>293</td></tr><tr><td></td><td>Blue Shale (use a second sheet if needed)</td><td>293</td><td>298</td></tr></tbody></table>			2	Type and color of material	From	To		Clay & sand streaks	0	135		Fine to coarse sand & cemented	135	140		Fine to coarse sand	140	165		Fine sand	165	180		Fine sand cemented	180	181		Sandy clay	181	194		Cemented sand fine	194	195		Sandy clay fine	195	206		Fine to coarse sand	206	223		Cemented sand fine	223	238		Sandy clay fine	238	241		Cemented sand fine	241	243		Fine to coarse sand	243	245		Cemented	245	253		Fine to coarse sand & gravel	253	293		Blue Shale (use a second sheet if needed)	293	298	5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
			2	Type and color of material	From	To																																																																			
				Clay & sand streaks	0	135																																																																			
				Fine to coarse sand & cemented	135	140																																																																			
				Fine to coarse sand	140	165																																																																			
				Fine sand	165	180																																																																			
				Fine sand cemented	180	181																																																																			
				Sandy clay	181	194																																																																			
				Cemented sand fine	194	195																																																																			
				Sandy clay fine	195	206																																																																			
	Fine to coarse sand	206	223																																																																						
	Cemented sand fine	223	238																																																																						
	Sandy clay fine	238	241																																																																						
	Cemented sand fine	241	243																																																																						
	Fine to coarse sand	243	245																																																																						
	Cemented	245	253																																																																						
	Fine to coarse sand & gravel	253	293																																																																						
	Blue Shale (use a second sheet if needed)	293	298																																																																						
6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well																																																																									
7 Casing: Material steel Height: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. 16 in. to 188 ft. depth Weight 7 gauge 16 in. to 298 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																																																									
8 Screen: Manufacturer W. A. Brown Type bridge Dia. 16" Slot/gauze 1/8 Length 2" Set between 203 ft. and 283 ft. Fittings: 10' Cook - 283 - 293 Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material 1/4 x 5/8																																																																									
9 Static water level: 145 ft. below land surface Date 11-20-75																																																																									
10 Pumping level below land surfaces: 195 ft. after 2 hrs. pumping 1300 g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield 1600 g.p.m.																																																																									
11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date ____																																																																									
12 Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade																																																																									
13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> & clay Depth: From 0 ft. to 10 ft.																																																																									
14 Nearest source of possible contamination: ft. 1800 Direction SE Type Home Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																																																									
15 Pump: <input type="checkbox"/> Not installed Manufacturer's name Byron Jackson Model number 8 HP 100 Volts 460 Length of drop pipe 288 ft. capacity 600 g.m.p. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																																																									
16 Remarks: elevation 3401 (TOPO) BROOK 293'																																																																									
17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Western Well & Pump Inc. 245 Business name License No. Address Box 852, Colby, Ks. Signed Roy F. Jackson Date 2-25-75 Authorized representative																																																																									