USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82q-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

AMERICAN Palamente Militaria esta de describer de del constituir en empresión como esta describencia constituir	County Fraction			on number	Township number	Range number	
1. Location of well:	Thomas	NEVA NEVASE	1/4	32	т 🤊 🙏 s:	R 36 W	
2. Distance and direction from nearest town or city: 2/2 Miles N. 3. Owner of well:							
K.K. Or street;					Brewster		
4. Locate with "X" in section below: Sketch map:					6. Bore hole dia. 28 in. Completion date		
N I I I I I I I I I I I I I I I I I I I					7Cable toolRotaryDrivenDugHollow rodJettedBored X_Reverse rotary		
W E					8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other		
SW SE 3-					9. Casing: Material Height: Above or below Threaded Welded Surface in.		
S 11 Mile					RMP PVC		
5. Type and color of material				То	Diain. toft. dep	oth gage No.	
tonca	It Clase		0	115	U.B. Brow		
m. A.	Dy Canhi 11h		11.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Set between	Length 10	
pourum de mais un de marcanis au réconse de la disserve au de la company	Salfa	et liberarena errena erren Errena errena erre	13:		Gravel pack? 122 Size ro	and 269 ft.	
A MANAGEMBER BEGINNE AND	L. Sur		15	5 165	11. Static water level:	mo./day/yr.	
MATERIAL I TROPOSTORIANO REALISES PARANCIA NO SPECIO A A ANALY TROPO ARRAMENTA CON TRA	Luciani.	+ Sandy Clay	163	175	ft. below land su 12. Pumping level below lan	nd surfaces:	
M-Savel - Carl Ol.			195	185	ft. after	hrs. pumping g.p.m. hrs. pumping g.p.m.	
			ones construinte en estado de la constitución de la constitución de la constitución de la constitución de la c	5 205	Estimated maximum yield		
Comment of the second	A comment		a de la companya de l	1 225	Yes No 14. Well head completion:	Date	
Comenter Sand				1235	Pitless adapter	/ Inches above grade	
M-Rayel				5 279		Bentonite Concrete	
Elist Ch				9280	Depth: From ft. to	le contamination:	
	C Walter Ball	AND IN COLUMN TO COLUMN AS TOO AND THE WAY AND	1		ft Direction Well disinfected upon compl	Type ### No	
BROCK 779					7. Pump: Manufacturer's name	Not installed	
					Model number	HP Volts ft. capacity 250 g.p.m.	
				marrowed (market) when residents of marrowing	Type:Submersible	Turbine	
(Use a second sheet if needed)					Jet Centrifugal	Reciprocating Other	
18. Elevation:	19. Remarks:	neer if needed)			20. Water well contractor's		
	÷				is true to the best of my know	my jurisdiction and this report wledge and belief.	
Topography:					Blue Jacy Dry	Mang Cotac 214	
Slope					Address Pry 503 C	1/1 5/2/20	
Valley					Signed Authorized re	presentative Vate ///	