

1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ NE $\frac{1}{4}$ NW Section Number 20 Township Number T 7 S Range Number R 42 E

Distance and direction from nearest town or city street address of well if located within city?

7 N Kanorado

2 WATER WELL OWNER: Greg Pettibone
 RR#, St. Address, Box # : 402 Walnut Str
 City, State, ZIP Code : Kanorado KS 67741
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	X		E
S			

4 DEPTH OF COMPLETED WELL 275 ft. ELEVATION: 4081

Depth(s) Groundwater Encountered 1 157 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 157 ft. below land surface measured on mo/day/yr 11/22/11

Pump test data: Well water was U.K. ft. after hours pumping gpm

Est. Yield 30 gpm: Well water was U.K. ft. after hours pumping gpm

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)	9 Dewatering	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No : If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: <u>Glued</u> Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 6.95 in. to 19 ft. Dia 5 in. to 255 ft. Dia 3 in. to ft.

Casing height above land surface 14 ft. weight 188 lbs./ft. Wall thickness or gauge No. 1.88

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS	11 Other (Specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut 0020	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 255 ft. to 275 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 210 ft. to 275 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 0 ft. to 20 ft. From 20 ft. to 60 ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? NE How many feet? 200'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	40	Soil + Clay			
40	80	Sand / Clchite			
80	160	Sand			
160	180	Hard			
180	200	Clay			
200	220	Clay			
220	275	med sand			
275	280	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/22/11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 743 This Water Well Record was completed on (mo/day/yr) 1/23/12 under the business name of Parrish Drilling by (signature) Wayne Parrish