USE TYPEWRITER OR BALL MOINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

	AAD				(Water well Contractors) Topeka, Kansas 66620		
County 1. Location of well:	'		number	Township number	Range number		
Sherman	SE 1/4 NE 1/4 NE	1/4	5	T 7	s R 42	₽1W	
2. Distance and direction from nearest town or city:		3. Owner of wel	I: Ru	dy SchriTTER			
Street address of well location if in city:	7%. 1	R.R. or street:	-	1) Arcade	. <i>)</i>		
4. Locate with "X" in section below:	7/4 N	City, state, zip	code: (Spodlund	in. Completion date 4	1-2-2	
N N	Sketch map: Cesspor L			Well depth 227 ft			
Ī III	Cesspo 2			7 Cable tool 🔀 Rot			
NW NE X-				Hollow rod Jet	tedBoredRever	se rotary	
	House			8. Use: X Domestic	Public supply Inde Air conditioning Stor	, I	
					Oil field water Oth		
SW SE	, X, ,			9. Casing: Material Z	i .	rłow	
<u> </u>	Well			Threaded Welded RMP PVC		in. _lbs./ft.	
1 Mile				Dia. in. to 29/ft.	depth Wall Thickness: inc	hes or	
5. Type and color of material		From	То	Dia in. to ft.		2	
11 - 1 - 1 - 11	- 1 -			10. Screen: Manufacture	s name		
MGRAVEL SANdy Elay	SANdSTONE	<i>\/77</i>	222	Type LUVER	Dia		
SAND		222	226	Slot/gauze 11 . 2 . Set between 29/	<u> </u>		
Fina SAND, M GRAVEL, S	BULSTONE	226	254		t. and	ft.	
Chay SANdsTone		254	263	11. Static water level:	mo./ surface Date	/day/yr.	
GRAVEL		263	265	12. Pumping level below			
FINE SAND M GRAVEL SE	who Plan	265	284	ft. after		g.p.m.	
1 - 1	7 2247	200	4.00	Estimated maximum yield		g.p.m.	
To Color		287	208	13. Water sample submitte YesNo	Date	/day/yr.	
tive SAND, SANDSTONE		288	3/3	14. Well head completion	· /2		
HARD SANDSTONE		3/3	314	Pitless adapter	Inches above g		
The Cond		ועפ	316	15. Well grouted? 46 With: Neat cement.	Bentonite X C	oncrete	
7/NE 24NA		3/7	5/6	Depth: From ft.	to ft.		
FINE SAND, SANDI Ch	ry, SANDSTONE	316	320	16. Nearest source of post	sible contamination: **XORTA** Type ************************************		
Fine SAND		320	326	Well disinfected upon con	npletion? <u>LS</u> Yes _	No	
Shale		30/	330	17. Pump: Manufacturer's name	Not installed JACKET	~ ~	
BRICK	Sect.	T		Model number	SC HP Su Volt. — ft. capacity SO	3.2.20 g.p.m. (
				Туре:		9.5	
				Submersible	Turbine Reciproc	catina	
(Use a secon	nd sheet if needed)		·	Centrifugal	Other	Š	
18. Elevation: 19. Remarks:	- 5- 1			20. Water well contractor			
3860 (T	UPO \			This well was drilled under is trugs to the best of my k	r my jurisdiction and this i nowledge and belief.	· 1	
Topography:	t .			STHOullen	6 hu /6	16 5	
Hill Slope				Business name	and Konson	nse No.	
				Signed Red Ch	Slow Date		
Vailey				Authorized	representative //-//-	75	