WATE	R WEL	L RECORD	Form W	WC-5	Division of Wa	ter Resources App. N	o	
ŧ .		OF WATER WELL:				Township No.	Range Number	
	ty: Mitc		SE 1/4 NE 1/4 NE				R6 DE ZW	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here								
Approx. 1.5 miles South and 3 miles East of Beloit, KS					Longitude: 98.024165 (in decimal degrees)			
App	rox. 1.5	miles South and 3 miles	East of Beloft, No	Elevation: 1351				
2 WATER WELL OWNER: Jerome Filert					Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Jerome Eilert RR#, Street Address, Box #: 3003 D Rd.					Collection Method: GPS unit (Make/Model:)			
City, State, ZIP Code : Beloit, KS 67420					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m								
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 46 ft. ft.								
	SECTION BOX: Depth(s) Groundwater Encountered (1)							
	N WELL'S STATIC WATER LEVEL26ft. below land surface measured on mo/day/yr6/11/2015							
Pump test data: Well water wasft. after							ping gpm	
W NV	V N	Bore Hole Diam	4.0.gpm. Well water wasft. after					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							njection well	
cw cp Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
Irrigation Industrial Domestic-lawn & garden Monitoring well Stock								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? \[\overline{\mathcal{A}} \text{ Yes } \square \text{ No} \]								
5 TYPE OF CASING USED: Steel V PVC Other								
CASING JOINTS: ☐ Glued ☐ Clamped ☐ Welded ☐ Threaded								
Casing diameter 5 in. to .26 ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface. 12 in., Weight 2.37 lbs./ft., Wall thickness or gauge No214								
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
	CDAN	CL DAGU DITEDMALC					to ft.	
	GKAVI	EL PACK INTERVALS:	From	π. τοπγ ft to	n., rrom ft From		to fi	
From								
Grout Intervals: From tt. to tt., From tt. to tt., From tt. to tt.								
What is the nearest source of possible contamination:								
✓ Septic tank								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
Direction from well North Distance from well .200.ft FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS								
FROM 0	TO 3	LITHOLOG Top soil	IIC LOG	FROM	TO LITHO.	LOG (cont.) or PLC	OGGING INTERVALS	
3	19	Clay, tan	, , , , , , , , , , , , , , , , , , ,					
19	50	Sand and Gravel- som	e clay layers					
50	51	Shale						
	ļ			<u> </u>			1	
ļ								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .6/11/15								
under the business name of Peterson McNett Drilling, Inc. by (signature) by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to								
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html								