EW-2	WATER WELL RECORD Form		4 82a-1212		
LOCATION OF WATER WELL:	Fraction NW 1/4 SW 1/4 SE	Section N		p Number	•
			т 7	s	R <b>7</b> E∕W
	or city street address of well if located wit oit, KS. Latitude N 39.45514° Le		0 106640		
		ongitude w s	0.10004	V-10-10	
WATER WELL OWNER: United A					
R#, St. Address, Box # : <b>7251 W</b> e					sion of Water Resources
ity, State, ZIP Code : Greeley,	, CO 80634		Application	Number: N	lot Applicable
LOCATE WELL'S LOCATON WITH	DEPTH OF COMPLETED WELL	20 -	EL EL (4.7101)	Ha	known
JAN -X. IN SECTION BOX:	DEPTH OF COMPLETED WELL	- 20 π	ELEVATION:		KIIOWII
	Deptin(s) Groundwater Encountered		II. Z		ال،
<b>†                                     </b>	WELL'S STATIC WATER LEVEL U	nk. ft. below	land surface measu	ed on mo/day/y	r
NW NE	Pump test data: Well water w	vas	ft. after	hours pu	umping gpm
l i l E	Est. Yield gpm: Well water w	vas	ft. after	hours pu	umpina apm
E B	Bore Hole Diameter <b>8</b> in. to WELL WATER TO BE USED AS: 5 Put 1 Domestic 3 Feed lot 6 Oil	20	ft and	in	to ft
-   i   i   i	WELL WATER TO BE USED AS: 5 Put	olic water supply	8 Air cond	ditioning 11	Injection well
swse	1 Domestic 3 Feed lot 6 Oil	field water supply	9 Dewate	ring 12	Other (Specify below)
sw <b>x</b> -se	2 Irrigation 4 Industrial 7 Lav	vn and garden (d	omestic) 10 Monito	oring well	
<b>*</b>	Was a chemical/bacteriological sample su				
3					• • • • • • • • • • • • • • • • • • • •
	submitted	*	Water Well Disinf		
TYPE OF BLANK CASING USED:	5 Wrought Iron	8 Concrete tile	e CASING	JOINTS: Glued	Clamped
1 Steel 3 RMP (SF	R) 6 Asbestos-Cement	9 Other (spec		Welde	
2 PVC 4 ABS	7 Fiberglass			Threa	ded
dank casing diameter 2	in. to <b>9.5</b> ft., Dia		ft Dia		in to ft
Social height shows land surface.	oprov 40 in maint 0	682	lba /ft \\/\all thislenge	No	0 1975 in
Asing height above land surface ap	pprox. 40 in., weight 0.	- Tayo	ibs./it. vvali inicknes	s or gauge No.	0.1070111.
YPE OF SCREEN OR PERFORATION	MATERIAL:	7 PVC	10 /	Asbestos-cemer	nt
1 Steel 3 Stainless	s steel 5 Fiberglass	8 RMP	(SR) 11 (	Other (specify)	
	zed steel 6 Concrete tile			None used (ope	
CREEN OR PERFORATION OPENING		d wrapped			11 None (open hole)
	Mill slot 6 Wire w	rapped	9 Drilled h		
2 Louvered shutter 4 K	Key punched 7 Torch of		10 Other (s	pecify)	
CREEN-PERFORATED INTERVALS:	From <b>9.5</b> ft. to	20	ft. From	ft. to	ft.
	From ft. to				
GRAVEL PACK INTERVALS:		20	ft. From	ft. to	o ft.
	From ft. to		ft. From	ft to	o ft.
CROUT MATERIAL 4 Nort co	ement 2 Cement grout	2 Pantanita	1 4 045	π. κ	у п.
GROOT MATERIAL. I Neat ce	ment 2 Cement grout	3 Bentonite	4 Other		
	t. to <b>7.5</b> ft. From			m	ft. to ft.
Vhat is the nearest source of possible co			Livestock pens	14 Aba	indoned water well
	4 Lateral lines 7 Pit privy		Fuel storage	15 Oil	well/ Gas well
2 Sewer lines 5	5 Cess pool 8 Sewage la	agoon 12	Fertilizer storage	16 Oth	er (specify below)
	6 Seepage pit 9 Feedyard		Insecticide storage		
Direction from well? east	,	Hov	v many feet?	unk	nown
FROM TO CODE	LITHOLOGIC LOG		ТО	PLUGGING IN	TERVALS
	k brown, lean clay, some silt				
	e to med. sand, some silt				
17 18 05 Fine	, some clay and fine sand				
	, come oray and mic same				
	, come day and mic sand		İ		
	, John Glay and The Garia			****	
	, some only and this same				-1
	, some only and this said				
	, some only and mile sund				
	, some only and mic sund				
18 20 02 Silt,		(1) constructed	2) reconstructed, or (3	s) plugged under	my jurisdiction and was
18 20 02 Silt,	'S CERTIFICATION: This water well was		·		
18 20 02 Silt,  7 CONTRACTOR'S OR LANDOWNER' completed on (mo/day/yr)	'S CERTIFICATION: This water well was 12/12/07	and this rec	ord is true to the best	of my knowled	ge and belief. Kansas
18 20 02 Silt,	'S CERTIFICATION: This water well was 12/12/07	and this rec	·	of my knowled	ge and belief. Kansas