

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL:
County: CLOUD

Distance and direction from nearest town or city street address of well if located within city?

Fraction
SW 1/4 NW 1/4 SW 1/4

2 WATER WELL OWNER: NATHAN HALE PESKA
RR#, St. Address, Box # : 170 N. 290th RD.
City, State, ZIP Code : MILTONVILLE, KS 67466

Section Number
26

Global Positioning Systems (decimal degrees, min. of 4 digits)
Latitude: 39.32540
Longitude: 97.40696
Elevation: 1436
Datum:
Data Collection Method:

Township Number
T 8 S
Range Number
R 1 E EW

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
N

--NW--		--NE--
X--SW--		--SE--

S

4 DEPTH OF COMPLETED WELL 122 ft.
Depth(s) Groundwater Encountered (1).....75..... ft. (2)..... ft. (3)..... ft.
WELL'S STATIC WATER LEVEL.....62..... ft. below land surface measured on mo/day/yr.....
Pump test data: Well water was..... ft. after..... hours pumping..... gpm
Est. Yield.....40..... gpm: Well water was..... ft. after..... hours pumping..... gpm
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr
Sample was submitted..... Water well disinfected? Yes X No

5 TYPE OF CASING USED:
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)
PVC 4 ABS 7 Fiberglass
Blank casing diameter 6 in. to 10.2 ft., Diameter in. to ft., Diameter in. to ft.
Casing height above land surface..... 24 in., Weight lbs./ft. Wall thickness or gauge No. SRR 26
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless Steel 5 Fiberglass PVC 9 ABS 11 Other (Specify)
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From..... 10.2 ft. to 122 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From..... 25 ft. to 122 ft., From ft. to ft.
From..... ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other
Grout Intervals: From 3 ft. to 25 ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 4 Abandoned water well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well
Direction from well? NORTHWEST How many feet? 90

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>8</u>	<u>CLAY</u>			
<u>8</u>	<u>10</u>	<u>LEAMSDONIA</u>			
<u>10</u>	<u>19</u>	<u>SANDSTONE</u>			
<u>19</u>	<u>28</u>	<u>SHALE, RED</u>			
<u>28</u>	<u>67</u>	<u>SANDSTONE</u>			
<u>67</u>	<u>75</u>	<u>SHALE, GRAY</u>			
<u>75</u>	<u>122</u>	<u>SANDSTONE H2O</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) .. 3/13/08 ... and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 760 This Water Well Record was completed on (mo/day/year) 3/18/08
under the business name of ASSOCIATED DRILLING INC. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.