


1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 NW 1/4 Section Number 29 Township Number T 8 S Range Number R 10 E  
 County: MITCHELL

Distance and direction from nearest town or city street address of well if located within city?  
AS BELOW

2 WATER WELL OWNER: FARMWAY COOP Board of Agriculture, Division of Water Resources  
 RR#, St. Address, Box #: WASHINGTON & BUFFALO Application Number:  
 City, State, ZIP Code: TIPTON, KS 67485

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 37 ft. ELEVATION: 1586.63  
 Depth(s) Groundwater Encountered 1. 105 ft. 2. 105 ft. 3. 105 ft.  
 WELL'S STATIC WATER LEVEL 36.05 ft. below land surface measured on mo/day/yr 5-11-95  
 Pump test data: Well water was 11 ft. after 10 hours pumping 10 gpm  
 Est. Yield 10 gpm: Well water was 11 ft. after 10 hours pumping 10 gpm  
 Bore Hole Diameter 11 in. to 11 in. to 11 in. to 11 in.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded  
 Blank casing diameter 4 in. to 20 ft., Dia 4 in. to 20 ft., Dia 4 in. to 20 ft.  
 Casing height above land surface 24 in., weight 4 lbs./ft. Wall thickness or gauge No. SCH 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) 10  
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 37 ft., From 20 ft. to 37 ft., From 20 ft. to 37 ft.  
 GRAVEL PACK INTERVALS: From 19 ft. to 37 ft., From 19 ft. to 37 ft., From 19 ft. to 37 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 2 ft. to 0 ft., From 2 ft. to 19 ft., From 2 ft. to 19 ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? N How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	18	BRN LOESS			
18	32	a.a. w/CHALK GRAVEL			
32	37	DK GRY SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-15-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 534 This Water Well Record was completed on (mo/day/yr) 6-12-95 under the business name of AGD SERVICES by (signature) [Signature]