WATE	R WEI	L RECORD	Form WWC-5	i		er Resources App. N		
1 LOCATION OF WATER WELL: County: Osborne			Fraction SE 1/4 SE 1/4 SW 1/4 N		tion Number 28	Township No. T 8 S	Range Number R 11 ☐E ☑W	
			f unknown, distance & direct	ion Glo	bal Positionin	g System (GPS) is	nformation:	
from	from nearest town or intersection: If at owner's address, check here .					Latitude: .39.328754 (in decimal degrees)		
l	4 miles West & 1/2 mile South of Tipton, Ks					Longitude: 98.551255 (in decimal degrees)		
Thines from a 1/2 him count of tiple 1,7 to					vation: 1696	ft 14, [7] NAD 83, [1 NAD 27	
2 WATER WELL OWNER: John Ketter					Collection Method:			
RR#, Street Address, Box #: 313 W. 160th Dr.					GPS unit (Make/Model:)			
City,	State, Z	IP Code : Tipton, I	Kansas 67485	_[] Digital Map/Pl	hoto, 🔲 Topograph	ic Map, Land Survey	
Est. Accuracy: <3 m, 3-5 m, 5-15 m, >15 m								
			COMPLETED WELL 4	5	A			
	WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.							
SEC.	SECTION BOX: Depth(s) Groundwater Encountered (1)							
	Pump test data: Well water wasft. after bours pumping							
NV	v N	FOT VIELD 3	5gpm. Well water was					
w	" \	E Bore Hole Diam	eter	ft., an	din	. to	.ft.	
"	WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well							
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
<u></u>	Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted								
Water well disinfected? Yes No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: 🗹 Glued 📋 Clamped 📋 Welded 📋 Threaded								
Casing diameter								
Casing height above land surface 12 in., Weight 2.37 lbs./ft., Wall thickness or gauge No. 0.214								
		EEN OR PERFORATION			.mn.			
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From 20 ft. to 45 ft., From ft. to ft.								
From								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other								
Grout Intervals: From								
What is the nearest source of possible contamination: Septic tank								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
Direc	tion from	n well Northeast	Dis	tance from	well7.00.ft.			
FROM	TO	LITHOLOG	IC LOG FRO	м то	LITHO. L	OG (cont.) <u>or</u> PLU	JGGING INTERVALS	
0	3	Topsoil						
3	20	Clay, tan					- W	
20	21	Fracture, water bearing						
21	58	Clay, silty						
58	80	Shale, gray						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗸 constructed, 🗆 reconstructed, or 🗆 plugged								
under my jurisdiction and was completed on (mo/day/year)								
Kansas Water Well Contractor's License No								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Taleshone 795 305 5524. Send one court to WATED WELL OWNED and enterin one for your records. Include fac of \$5.00 for each constructed mall. Visit us at								