

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:		County Osborne	Fraction 1/4 SE 1/4 SE 1/4	Section number 20	Township number T 8 S R 12 E/W	Range number
2. Distance and direction from nearest town or city: 7 South / East of Osborne			3. Owner of well: MORTON De MASS			
Street address of well location if in city:			R.R. or street: City, state, zip code: Osborne - Kansas - 67473			
4. Locate with "X" in section below:		Sketch map:			6. Bore hole dia. 9 1/2 in. Completion date 18th of April	
					Well depth 67 ft.	
5. Type and color of material		From		To		7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary
top soil		0		2		8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
clay, light brown		2		5		9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 2ft. in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight <input type="checkbox"/> lbs./ft. Dia. 6 in. to 6 7/8 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 3/16
clay, light brown + very fine gravel		15		20		10. Screen: Manufacturer's name JESSY Lowell Superior Well Casing Type PVC Dia. 6 inch. Slot gauze 1/16" Length 37 Set between 30 ft. and 67 ft. ft. and <input type="checkbox"/> ft.
clay mixed with fine to 1/2" dia. gravel		20		50		Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/4" to 1/2"
clay, mixed with coarse gravel		50		52		11. Static water level: <input type="checkbox"/> mo./day/yr. 27 ft. below land surface Date 4-18-77
gravel washed white 1/8" to 1/2" dia.		52		67		12. Pumping level below land surfaces: 27 ft. after 3 hrs. pumping 20 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 30-35 g.p.m.
						13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>
						14. Well head completion: <input type="checkbox"/> Pitless adapter 24" inches above grade
						15. Well grouted? <input checked="" type="checkbox"/> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 3 1/2 ft. to 14 ft.
						16. Nearest source of possible contamination: Septic ft. 1000 Direction East Type tank Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
						17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name <input type="checkbox"/> Model number <input type="checkbox"/> HP <input type="checkbox"/> Volts <input type="checkbox"/> Length of drop pipe <input type="checkbox"/> ft. capacity <input type="checkbox"/> g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
18. Elevation:		19. Remarks: shool house near well is torn down only basement walls left.		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is to the best of my knowledge and belief. Schurr Swilling 348 Business name License No. Address Box 17 Osborne, Ks. Signed Mike Schurr Date 4-18-77 Authorized representative		

T 8 R 12 W 20 SE SE