WATER WELL REC		Form WWC			Division of Water Resources App. No		Well ID Stock	
Original Record Correction Change in Well Use 1 LOCATION OF WATER WELL: Fraction					ection Numbe		umber Range Number	
County: Osborne								
2 WELL OWNER: Last Name: Wilson Business: Address: 3924 Snowy Reach Address: Address: 3924 Snowy Reach Address: Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: Approximately 6 miles south and 1 mile west of Osborne.								
City: Manhattan State: KS ZIP: 66503								
3 LOCATE WELL WITH "X" IN SECTION BOX: NNWNE W × E	red Well: ntered: 1) ft., or 4) EVEL: 16.1 ured on (mo-day- ured on (mo-day- ured on t checked ft ing	ft. Dry Well ft. ft. yr) 05-07-	Longit Horizo Source M G	5 Latitude: 39.345253 (decimal degrees) Longitude: -98.725721 (decimal degrees) Horizontal Datum. ☐ WGS 84 ☐ NAD 83 ☒ NAD 27 Source for Latitude/Longitude: ☒ GPS (unit make/model: (WAAS enabled? ☒ Yes ☐ No) ☐ Land Survey ☐ Topographic Map ☐ Online Mapper:				
SWSE S mile	after Estimated Y Bore Hole I	Well water w	vas fiing g m in. to 53	pm ft. and	6 Elevat	tion: Unknown	ft. Ground Level TOC GPS Topographic Map	
7 WELL WATER TO BE USED AS:								
1. Domestic:					11. Test Ca Ca 12. Geotl a) Cl b) Op	10. Oil Field Water Supply: lease 11. Test Hole: well ID		
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☒ No If yes, date sample was submitted:								
Water well disinfected? Yes □ No 8 TYPE OF CASING USED: □ Steel ☑ PVC CASING JOINTS: ☑ Glued □ Clamped □ Welded □ Threaded □ Other								
Casing diameter 5 in. to 40 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in. Weight 2.36 lbs./ft. Wall thickness or gauge No215 TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Screen-Perforated Intervals: From 40 ft. to 50 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 53 ft., From ft. to ft., From ft. to ft.								
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 4 ft. to 24 ft From ft. to ft. From ft. to ft.								
Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) None Known								
10 FROM TO	I	ITHOLOGIC LO		FROM	TO ft.	LITHO, LOG (cont.	.) or PLUGGING INTERVALS	
	psoil						,	
	Clay, dark gray							
Notes:								
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was and constructed, or plugged under my jurisdiction and was completed on (mo-day-year) 05-07-18 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo-day-year) 05-09-18 under the business name of Clarke Well & Equipment, Inc. Mail I white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,								
Mail 1 white copy alor	ng with a fee of	\$5.00 for each const	ructed well to: Kan	sas Departme	nt of Health and	Environment, Bureau o		
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524. Visit us at http://www.kdheks.izov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015								