

1 LOCATION OF WATER WELL: County: Cloud Fraction SW 1/4 SW 1/4 SE 1/4 Section 13 Township Number 8 Range Number 2

Distance and direction from nearest town or city street address of well if located within city? From Miltonvale go 2 miles west

2 WATER WELL OWNER: Doyle Scott RR 1 Box 51 Miltonvale, KS 67466

Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in SE corner]

4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION: 100 ft. WELL'S STATIC WATER LEVEL: 100 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 10 ft. after 100 hours pumping gpm: 105 Est. Yield: 105 gpm Well water was 160 ft. after 160 hours pumping gpm: 160 Bore Hole Diameter: 10 in. to 160 ft. and 160 in. to 160 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter: 5 in. to 120 ft. Dia. 5 in. to 120 ft. Dia. Casing height above land surface: 120 in. weight 54 lb weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft. From 120 ft. to 140 ft. From 120 ft. to 140 ft. From 120 ft. to 140 ft.

GRAVEL PACK INTERVALS: From 25 ft. to 140 ft. From 25 ft. to 140 ft. From 25 ft. to 140 ft. From 25 ft. to 140 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 25 ft. From 0 ft. to 25 ft. From 0 ft. to 25 ft. From 0 ft. to 25 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? WEST How many feet? 150'

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/18/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/yr) 6/25/98 under the business name of Haldeman Well Drilling by (signature) Craig A. Haldeman

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.