

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

986

1 LOCATION OF WATER WELL: County: Rooks Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 22 Township Number T 8 S Range Number R 20 E/W Distance and direction from nearest town or city street address of well if located within city? 2 miles east-1 mile north of Damar

2 WATER WELL OWNER: Gayleen Gosslin RR#, St. Address, Box #: 3520 Q Rd City, State, ZIP Code: Boque, KS 67625 Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E S

4 DEPTH OF COMPLETED WELL 35 ft. Depth(s) Groundwater Encountered (1) 15 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 2 ft. below land surface measured on mo/day/yr. 5/23/09 Pump test data: Well water was 15 ft. after 1 hours pumping 10 gpm Est. Yield 10 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 15 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr Sample was submitted Water well disinfected? Yes X No

5 TYPE OF CASING USED: 2 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 5 Fiberglass Blank casing diameter in. to 35 ft., Diameter in. to 24 in., Diameter in. to 21 in. Casing height above land surface in., Weight 2.91 lbs./ft. Wall thickness or gauge No. 21 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 35 ft. to 15 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 35 ft. to 14 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 14 ft. to 0 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: none 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide storage 16 Other (specify) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/gas well Direction from well? How many feet?

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-6 Top soil, 6-8 gumbo, 8-16 rock layers some clay, 16-19 sand, 19-22 shale, 22-35 gray rock. Includes 'CORRECTED' stamp and 'RECEIVED JUN 24 2009 BUREAU OF WATER' stamp.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... 5/23/09 ... and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 0100. This Water Well Record was completed on (mo/day/year) 5/23/09 under the business name of Karst Water Well Drilling & Storage, by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.