


1 LOCATION OF WATER WELL: County: Graham Fraction: NW 1/4 NW 1/4 NW 1/4 Section Number: 20 Township Number: T 8 S Range Number: R 21 EW

Distance and direction from nearest town or city street address of well if located within city? 1/2 miles south of Boyer, Ks

2 WATER WELL OWNER: Mike Daignon RR#, St. Address, Box #: P.O. Box 150 City, State, ZIP Code: Boyer, Ks. 67625 Board of Agriculture, Division of Water Resources Application Number: Test hole

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION: 70 ft. Depth(s) Groundwater Encountered: 1. 32 ft. 2. NA ft. 3. NA ft. WELL'S STATIC WATER LEVEL: NA ft. below land surface measured on mo/day/yr Pump test data: Well water was NA ft. after NA hours pumping NA gpm Est. Yield 100+ gpm: Well water was NA ft. after NA hours pumping NA gpm Bore Hole Diameter: 6 in. to 70 ft., and NA in. to NA ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Lithological Note Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted NA Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass None Threaded Blank casing diameter: 8" in. to NA ft., Dia. NA in. to NA ft., Dia. Casing height above land surface: 0 in., weight NA lbs./ft. Wall thickness or gauge No. NA TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) NA 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) NA 7 Torch cut 10 Other (specify) NA SCREEN-PERFORATED INTERVALS: From 40 ft. to 48 ft., From 45 ft. to 52 ft., From NA ft. to NA ft. GRAVEL PACK INTERVALS: From 48 ft. to 70 ft., From 48 ft. to 48 ft., From 45 ft. to 32 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 48 ft. to 45 ft., From 32 ft. to 0 ft., From NA ft. to NA ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage nothing observed

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	1/2" ss	70	48	CMA Gravel
7	14	1/2" br. clay	48	45	bentonite chip
14	32	clay intermitten w fish	45	32	CMA Gravel
32	34	1/2" frag. mal sd.	32	0	bentonite chip
34	36	Sand of F. to med			
36	45	Sd course			
45	48	Clay gray to offwhite			
48	55	fulgise clay			
55	62	sd br. clay (80% sd) (20% clay)			
62	68	sd. if to course, well sorted			
68	69	weathered shale			
69	70	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-15-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 608 This Water Well Record was completed on (mo/day/yr) 8-12-96 under the business name of Yellow Jacket Drilling by (signature) Ernest H. Haddock, Jr.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R EW SEC.