Dock Content
2 WELL OWNTRY Last Name:
Street or Rural Address where well is located if unknown, disance and drection from nearest town or intersections): If at owner's address, check here: [Address of 1000 SW Jackson St. Suite 410 Address of 1000 st. St. and 280th Ave Address of 1000 SW Jackson St. Suite 410 Address of 1000 st. St. and 280th Ave Address of 1000 st. Address of 1000 st. St. and 280th Ave Address of 1000 st. Address of 1000
Sustinest NoHE Sustinest NoHE Sustinest NoHE Address: 1000 SW Jackson St. Suite 410 Address: 1000 St. Suite 410 Swite 410
Bassacsex KDHE Address: 1000 SW Jackson St., Suite 410 Address: 1001 SW Jackson St., Suite 410 Address: 1002 SW Jackson St., Suite 410 Address: 1002 SW Jackson St., Suite 410 Approximately 1300 ft. east and 300 north of intersection of Missac Market Mark
Address: 1000 SW Jackson St. Suite 410 Approximately 1300 ft. east and 300 north of intersection of Mist. Address: City: Topeka State: KS
Address: Coy: Topeka
A DEPTH OF COMPLETED WELL: 84 ft. Cpth(s) Groundwater Encountered: 1) Nall ft. Nall N
3 LOCATE WELL WITH *X' IN SECTION BOX: Depth(s) Groundwater Encountered: 1) NaT ft 2) ft 3) ft
Depth(s) Groundwater Encountered: 1) Nit ft.
2) ft 3) ft cr dr dr dr dr dr dr dr
N
NW NE NE Dump test data: Well water was ft. after hours pumping gpm Well water was ft. after hours pumping gpm S well vater was ft. after hours pumping gpm S well vater was ft. after hours pumping gpm S well vater was ft. after hours pumping gpm bore Hole Diameter 8.75 in. to ft. Source: Land Survey GPS Topographic Map Other Topographic Map Topographic
Pump test data: Well water was ft after hours pumping gpm Well water was ft after hours pumping gpm well made mous pumping gpm bestimated Yield: gpm
after
Well water was f. after hours pumping gpm Bore Hole Diameter hours pumping gpm Bore Hole Diameter hours pumping gpm Bore Hole Diameter hours pumping gpm hore Hole Diameter hours pumping hore Hole Diameter hours
after
Estimated Yield:
S
TWELL WATER TO BE USED AS: Dublic Water Supply: well ID
Domestic: 5. Public Water Supply: well ID 10. Oil Field Water Supply: lease Household Cawn & Garden 7. Aquifer Recharge: well ID Cased Uncased Geotechnical Livestock 8. Monitoring: well ID MW-9 12. Geothermal: how many bores? 2. Irrigation 9. Environmental Remediation: well ID a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water Industrial Recovery Injection In
Household
Lawn & Garden
2.
2.
3. Feedlot
A.
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☐ No If yes, date sample was submitted: Water well disinfected? ☐ Yes ☐ No 8 TYPE OF CASING USED: ☐ Steel ☐ PVC ☐ Other
Water well disinfected? Yes No No No No No No No N
STYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Thread Casing diameter 2 in. to C4 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 9 in. Weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Other (Specify) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Continuous Slot Mill Slot Gauze Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 64 ft. to 84 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 62 ft. to 84 ft., From ft. to ft., From ft. to ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Direction from well? 998t Distance from well? 1300.ft. ft. 100 FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC COG. TO Thologic INTERVALS Thologic Intervals Thologic Intervals Thologic In
Casing diameter 2 in to 64 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 9 in. Weight lbs./ft. Wall thickness or gauge No. 9ch. 40. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel
Casing diameter 2 in to 64 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 9 in. Weight lbs./ft. Wall thickness or gauge No. 9ch. 40. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel
□ Steel □ Stainless Steel □ Fiberglass ■ PVC □ Other (Specify) □ Brass □ Galvanized Steel □ Concrete tile □ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: □ Continuous Slot ■ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify) □ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From
□ Brass □ Galvanized Steel □ Concrete tile □ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: □ Continuous Slot ■ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify) □ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From .64 .64
SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 64 ft. to 84 ft., From ft. to ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 62 ft. to 84 ft., From ft. to ft., From ft. to ft., From ft. to ft. 9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Royal Acid. Direction from well? 98st Distance from well? 1300 ft. 10 FROM TO LITHOLOGIC LOG FROM TO LITHOLOG (cont.) or PLUGGING INTERVA
☐ Continuous Slot Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify) ☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole) SCREEN-PERFORATED INTERVALS: From
Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From .64
SCREEN-PERFORATED INTERVALS: From .64 ft. to .84 ft., From ft. to ft., From ft. ft. ft. ft. ft. ft. ft. ft. ft.
GRAVEL PACK INTERVALS: From
9 GROUT MATERIAL: □ Neat cement □ Cement grout ■ Bentonite □ Other Grout Intervals: From □ 0 ft. to 62 ft., From □ ft. to □ ft., From □ ft. to □ ft. Nearest source of possible contamination: □ Septic Tank □ Lateral Lines □ Pit Privy □ Livestock Pens □ Insecticide Storage □ Abandoned Water Well □ Watertight Sewer Lines □ Cess Pool □ Sewage Lagoon □ Fuel Storage □ Abandoned Water Well □ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well ■ Other (Specify) Royal Acid □ Distance from well? 1300 ft. □ ft. 10 FROM TO LITHOLOGIC LOG FROM TO LITHOL LOG (cont.) or PLUGGING INTERVA
Grout Intervals: From U ft. to 102 ft., From ft. to 11. ft. from ft. to 12. ft., From ft. to 12. ft., From ft. to 13. ft. from ft.
Nearest source of possible contamination: Septic Tank
□ Septic Tank □ Lateral Lines □ Pit Privy □ Livestock Pens □ Insecticide Storage □ Sewer Lines □ Cess Pool □ Sewage Lagoon □ Fuel Storage □ Abandoned Water Well □ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well □ Other (Specify) Royal Acid □ Distance from well? 1300 ft ft □ FROM TO LITHOLOGIC LOG FROM TO LITHOL LOG (cont.) or PLUGGING INTERVAL
□ Sewer Lines □ Cess Pool □ Sewage Lagoon □ Fuel Storage □ Abandoned Water Well □ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well ■ Other (Specify) Royal Acid □ Distance from well? 1300 ft ft 10 FROM TO LITHOLOGIC LOG FROM TO LITHOL LOG (cont.) or PLUGGING INTERVAL
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well ■ Other (Specify) Royal Acid. □ □ Distance from well? 1300 ft. ft. 10 FROM TO LITHOLOGIC LOG FROM TO LITHOL LOG (cont.) or PLUGGING INTERVAL
■ Other (Specify) Royal Acid. Direction from well? east Distance from well? 1300 ft. ft. 10 FROM TO LITHOLOGIC LOG FROM TO LITHOL LOG (cont.) or PLUGGING INTERVA
Direction from well? east Distance from well? .1300 ft. ft. 10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVA
10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVA
The second secon
9 20 Sand, light brown,damp, fine
20 27 Sandy Clay, brown, coarse sand, wet
plastic
27 84 Sand, light brown, coarse with gravel, wet
Notes:
17000
11 CONTRACTOR'S OR I ANDOWNED'S CERTIFICATION. This pasts well use a constructed or a place
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugg under my jurisdiction and was completed on (mo-day-year) 1-9-2020 and this record is true to the best of my knowledge and believed.
Kansas Water Well Contractor's License No. 604 This Water Well Record was completed on (mo-day-year). 1.1.2.2
under the business name of Environmental Priority Service, Inc. Signature Signature
where the exempted matter of with restrictive transfer and the control of the con
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment Bureau of Water GWTS Section
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.