

HILL CITY SOUTH

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment  
(Water well Contractors)  
Topeka, Kansas 66620

ACC

1. Location of well: County <u>GRAHAM</u> Fraction <u>SW 1/4 SW 1/4 NE 1/4</u> Section number <u>12</u> Township number T <u>8</u> S R <u>23</u> E/W	
2. Distance and direction from nearest town or city: <u>1/2 mile East of Hill City, Kan</u> 3. Owner of well: <u>JIMMY JONES</u> R.R. or street: <u>321 West</u> City, state, zip code: <u>Hill City, Kan. 67642</u>	
4. Locate with "X" in section below: Sketch map: <u>RAIN POAT</u> 	
5. Type and color of material	
<u>Brown clay</u>	From 0 To 16
<u>Blue mud &amp; Fine white sand</u>	16 25
<u>Hard Blue shale</u>	25 26
<u>BRICK 15'</u>	
<u>18'</u>	
<u>7' set back</u>	
<u>Not in Og</u>	
(Use a second sheet if needed)	
18. Elevation: Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input checked="" type="checkbox"/> Valley	19. Remarks: <u>Land owners poured concrete slab 2160' (TOPO) 25 2135'</u>
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>D.L. DAILING CO. 303</u> Business name License No. Address <u>Hill City, Kan</u> Signed <u>Alan J. Joanni</u> Date <u>4-18-77</u> Authorized representative	

6. Bore hole dia. 4" in. Completion date 2-12-77  
Well depth 26 ft.

7.  Cable tool  Rotary  Driven  Dug  
 Hollow rod  Jetted  Bored  Reverse rotary

8. Use:  Domestic  Public supply  Industry  
 Irrigation  Air conditioning  Stock  
 Lawn  Oil field water  Other

9. Casing: Material PTS Height:  Above or below  
Threaded  Welded  Surface 60 in.  
RMP 5  mm Weight          lbs./ft.  
Dia. 5 in. to 26 ft. depth Wall Thickness: inches or  
Dia.          in. to          ft. depth gage No. 250

10. Screen: Manufacturer's name JESS  
Lowell  
Type Cosden 92SD Dia. 5"  
Slot/gauze X Length 10'  
Set between 16 ft. and 26 ft.  
         ft. and          ft.  
Gravel pack?  Size range of material 1/4 to 3/8

11. Static water level: 18 ft. below land surface Date 2-12-77 mo./day/yr.

12. Pumping level below land surface:  
         ft. after          hrs. pumping          g.p.m.  
         ft. after          hrs. pumping          g.p.m.  
Estimated maximum yield          g.p.m.

13. Water sample submitted:          mo./day/yr.  
Yes  No  Date         

14. Well head completion:  
 Pitless adapter          inches above grade

15. Well grouted? yes  
With:  Neat cement  Bentonite  Concrete  
Depth: From 4 ft. to 15 ft.

16. Nearest source of possible contamination:  
ft. 300 Direction E Type Cosspod  
Well disinfected upon completion?  Yes  No

17. Pump:  Not installed  
Manufacturer's name           
Model number          HP          Volts           
Length of drop pipe          ft. capacity          g.p.m.  
Type:  
 Submersible  Turbine  
 Jet  Reciprocating  
 Centrifugal  Other

T 8  
R 23  
E  
12  
SW SW NE  
1/4 1/4 1/4