WATER WELL RECORD		Form WWC-5		Division of Water Resources App. No.		
1 LOCATION OF WATER WELL: County: GRAHAM		Fraction NW ¼ NW ¼ NW ½	1/4	Section Number 34		
Street/Rural A	Address of Well Location;		Global Positioning System (GPS) information:			
	town or intersection: If at o		Latitude: (in decimal degrees)			
1/2 mile South, 1 mile West, 1 1/2 mile South of Penokee			Longitude: (in decimal degrees)			
7/2 Time Goddi, 1 Time Wood, 1 //2 Time Goddi of 1 Grones				Elevation:		
A WATER WELL OWNER.				<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27		
2 WATER WELL OWNER: JIM POPP			Collection Method:  GPS unit (Make/Model:)			
RR#, Street Address, Box #: 205 LINCOLN STREET						ic Map,  Land Survey
City, State, Z	QOIITI	ER KS 67752				5-15 m,
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 83 ft.						
	SECTION BOX: Depth(s) Groundwater Encountered (1).56 ft. (2)					
WELL'S STATIC WATER LEVEL						
					nours pum	ping gpm
NW N	E	gpm. Well water wasft. after				
w	E   Bore Hole Diam					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
SW SE						
Irrigation   Industrial   Domestic-lawn & garden   Monitoring well   Monitoring well						
Was a chemical/bacteriological sample submitted to Department?  Yes No						
S If yes, mo/day/yr sample was submitted						
Water well disinfected?  Yes No						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded						
Casing diameter .5 in. to .83 ft., Diameter in. to ft., Diameter in. to ft.						
Casing height above land surface. 18 in., Weight .160 lbs./ft., Wall thickness or gauge No.						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)						
Louvered shutter    Key punched    Saw cut    Other (specify)						
SCREEN-PERFORATED INTERVALS: From83						
From						
From						
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other						
Grout Intervals:			f	ît. to fît.	, From	ft. toft.
What is the nearest source of possible contamination:						
Septic tank						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well						
	m well					•••••
FROM TO	LITHOLOG		FROM			JGGING INTERVALS
		IC LOO	KOW	LITHO, L	OG (WIII.) OI FLO	COUNC INTERVALS
	SURFACE CLAY					
10 30	HARD YELLOW CLAY					
30 35	HARD WHITE LIMEST	UNE				
35 50	GRAY SANDY LOMB					
50 55	MED SAND					
55 75	MED TO LARGE SAN					
75 80	SOFT BROWN SHALE					
80 83	BLUE SHALE					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/day/year) .07:08:09 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No444 This Water Well Record was completed op (mo/day/year) .07-08-09						
under the business name of ANDY ANDERSON DRILLING by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						