			ECORD			-5		of Water Res				
			VATER W			1/4 SW 1/4	Section	n Number	Township	Number S	Range Number R 24 □E ⊠w	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here □.  1 mile east of Morland school—1/2 south—east into							Global Positioning System (GPS) information: Latitude: (in decimal degrees) Longitude: (in decimal degrees) Elevation:					
I	VATER WELL OWNER RR#, St. Address, Box # 1330 140 <sup>th</sup> Ave City, State, ZIP Code Morland, KS 67650						Datum: □ WGS 84, □ NAD 83, □ NAD 27  Collection Method: □ GPS unit (Make/Model: □ Digital Map/Photo, □ Topographic Map, □ Land Survey  Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m					
l	LOCATI					07						
	WITH A SECTIO	N "X" IN N BOX:	Depth(s)	Groundwat	MPLETED WELI ter Encountered (	. <u>86</u> 1)		ft. (2)	ft.	ft. (3)	ft.	
	<u> </u>		WELL'S	STATIC V	VATER LEVEL	72	ft, belov	v land surface	e measured o	on mo/day/yi	· `	
W		NE	EST. YIELD gpm: Well water was				ft. after hours pumping g  ft. after hours pumping g  atter supply  Geothermal Injection well  y Dewatering Other (Specify below)  garden Monitoring well  o Department? Yes No					
	S If yes,			es, mo/day/	o/day/yr sample was submitted							
		·			pured - Press							
5 TYPE OF CASING USED: □ Steel □ PVC □ Other  CASING JOINTS: □ Glued □ Clamped □ Welded □ Threaded  Casing diameter 4.5 in. to 66 ft., Diameter in. to ft.  Casing height above land surface 18 in., Weight 2.38 lbs./ft. Wall thickness or gauge No248  TYPE OF SCREEN OR PERFORATION MATERIAL: □ Steel □ Stainless Steel □ PVC □ Other (Specify) □ Brass □ Galvanized Steel □ None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:  Continuous Slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)  Louvered shutter  Key punched  Wire wrapped  Saw cut  Other (specify)												
SCREEN-PERFORATED INTERVALS: From 66 ft. to							86       ft., From       ft. to       ft.         ft., From       ft. to       ft.         86       ft., From       ft. to       ft.         ft., From       ft. to       ft.					
6 GROUT MATERIAL: ☐ Neat cement Cement grout ☑ Bentonite ☐ Corout Intervals From 0 ft. to 20 ft. From ft. to												
Gro	ut Interval	s Fro	m <b>0</b>	ft. to	tion:		ft. to	ft.	From		ft. toft.	
	☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fert							estock pens				
Fl	ROM	TO		LITHOLO	GIC LOG	FRC	М Т	O LITHO	). LOG (con	ıt.) <u>or</u> PLUC	GING INTERVALS	
-	2		Surface Loess									
	16	28 (	Clay & san									
	28 33 Caliche & sandstone 33 44 Caliche											
	44	55 \$	Sandy clay	w/caliche	strks							
	55 70		Clay Sand									
	, ,	00 K	, esal Ul									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or □ plugged under my jurisdiction and was completed on (mo/day/year) 5/17/12 And this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/year) 6-5-/2 under the business name of Woofter Pump & Well Inc. by (signature)  INSTRUCTIONS: Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Viealth and Environment, Bureau of												
Wat	ter, Geologi	Section, 10	00 SW Jackso	n St., Suite 4	rrect answers. Send thr 420, Topeka, Kansas 6 astructed well. Visit u	6612-1367.	Telephone	2785-296-5522	<ol><li>Send one to</li></ol>	of Mealth and WATER W	Environment, Burcau o ELL OWNER and retain	

Check:  $\square$  White Copy,  $\square$  Blue Copy,  $\square$  Pink Copy