


1 LOCATION OF WATER WELL: County: Graham	Fraction SE 1/4 NW 1/4 NW 1/4	Section Number 22	Township Number T 8 S	Range Number R 25 EW
--	---	-----------------------------	---------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1 1/2 miles east, from Morland

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Richard Mowry HC 1 Box 100 Morland, Ks. 67650	KCC Conservation Division 2301 E. 13th Hays, Ks. 67601	Board of Agriculture, Division of Water Resources Application Number:
---	--	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 31 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 80 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 4.5 in. to 40 ft., Dia 4.5 in. to 74' to 80' ft., Dia in. to ft.			
Casing height above land surface 18 in., weight 2.38 lbs./ft. Wall thickness or gauge No. 248			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 40 ft. to 74 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 80 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft.				
What is the nearest source of possible contamination: NONE	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Surface			
1	6	Silty Sand			
6	15	Med. to Coarse Sand & Gravel			
15	15.5	Hard Layer			
15.5	18	Blue Clay			
18	21	Med. Sand			
21	36	Blue Clay/Fine Sand Strks.			
36	38	Sand - Fine to Med.			
38	41	Blue Clay			
41	51.5	Med. Loose Sand			
51.5	56	Blue Clay/Sand Strks.			
56	72	Med. Sand & Gravel/Blue Clay Strks.			
72	80	Shale - Hard Grey & White			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-6-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 10-12-92 under the business name HOOPER PUMP & WELL INC. by (signature) <i>Jim C. Woelfel</i>
