HOXIE 23W

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

T R EW sec 1/4 1/4 1/4 No.

WATER WELL RECORD
KSA 82a-1201-1215

13AB CAB

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County	Township name	Fraction	Section number	Town number	Range number
	Sheridan	Kenneth NWL	NE 1/4 NW 1/4	28	8	28

Distance and direction from nearest town or city: 1 south 5/8 west
Hoxie, Kansas
Street address of well location if in city:

3 Owner of well: Clarence Schamberger
Address: Hoxie, Kansas

Locate with "X" in section below: Sketch map:

N
W E
S
1 Mile

4 Well depth: 228 ft. Date of completion 2-28-75
Well diameter 20 in.

5 ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug
☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary

6 Use: ☐ Domestic ☐ Public supply ☐ Industry
☒ Irrigation ☐ Air conditioning ☐ Commercial
☐ Test well ☐

7 Casing: Material steel Height: above/below
Threaded ☐ Welded ☒ Surface 12 in.
Diam. 12 3/4 Weight 33 lbs./ft. 1
0 in. to 228 ft. depth Drive shoe? ☐ Yes ☒ No
___ in. to ___ ft. depth

8 Screen:
Manufacturer W. A. Brown
Type Luver Dia. 12 3/4
Slot/gauze 7 - 1/8 Length 60
Set between 168 ft. and 228 ft.
Fittings:
Gravel pack ☒ Yes ☐ No Size range of material 1/4 X 5/

2 Type and color of material	From	To
Topsoil	0	115
Sandy clay & sandstone	115	128
Clay, fine sand, med. gravel red	128	142
Sandy clay, sandstone	142	158
Med. gravel red	158	173
Sandy clay, rock, sand stone	173	176
Clay, med. gravel	176	180
Clay	180	195
Sandy clay	195	204
Streak clay, med. gravel, gravel red	204	222
Ochre - shale	222	230
BROCK 222'		
(use a second sheet if needed)		

9 Static water level:
114 ft. below land surface Date 1-15-75

10 Pumping level below land surfaces:
225 ft. after 9 hrs. pumping 1200 g.p.m.
___ ft. after ___ hrs. pumping ___ g.p.m.
Estimated maximum yield 1200 g.p.m.

11 Water sample submitted:
☐ Yes ☒ No Date ___

12 Well head completion:
☐ Pitless adapter 12 Inches above grade

13 Well grouted? ☒ Yes ☐ No
☒ Neat cement ☐ Bentonite ☐ ___
Depth: From 0 ft. to 10 ft.

14 Nearest source of possible contamination:
ft. ___ Direction ___ Type None
Well disinfected upon completion? ☐ Yes ☒ No

15 Pump: ☐ Not installed
Manufacturer's name Goulds
Model number 8x16½ HP 100 Volts 440
Length of drop pipe 220 ft. capacity 1200 g.p.m.
Type:
☐ Submersible ☒ Turbine
☐ Jet ☐ Reciprocating
☐ Certrifugal ☐ Other

16 Remarks: elevation
2705 (TOPO)
2748

Topography:
☐ Hill
☐ Slope
☒ Upland
☐ Valley

17 Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Blue Jay Drilling Co. Inc. 214
Business name License No.
Address Colby, Kansas
Signed Marilyn Rall Date 3-14-75
Authorized representative

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5