WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | Section | on number | Township number | Range number |
|---|-----------------|--|---------|---------------------|--|--|
| 1. Location of well: | Slouds | 900 1/4 20 W1/4 m W | 4/د | 14 | T S s | R 96 EAR |
| 2. Distance and direction from nearest town or city: Street address of well location if in city: R.R. or street: | | | | | | |
| 2. Distance and direction from nearest town or city: Street address of well location if in city: 4 E La south City, state, zip code: Have, K5 67740 | | | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | 6. Bore hole dia. 9 in. Completion date 5-8/ | |
| N N | | | | | Well depth 245 ft. | |
| | 1 | | | | 7 Cable tool X Rotary | |
| NW | - NE | | | | | Bored Reverse rotary |
| W I I E | | | | | 8. Use: X Domestic Public supply Industry Irrigation Air conditioning Stock | |
| SW SE | | | | | LawnOil field water Other 9. Casing: Material Height: Above or below | |
| | | | | | | |
| S | | | | | | Surface 13 in. Weight 300 lbs./ft. |
| 5. Type and color of | | | From | То | Diain. toft. de Diain. toft. de | pth Wall Thickness; inches or oth gage No. |
| | A | TO THE PROPERTY OF THE PROPERT | | , , , | 10. Screen: Manufacturer's, | name |
| dep d | Loil | | 0 | 36 | Type PVC | |
| Ohndu | Clark | | 36 | 85 | Slot/gauze 110 - 18 Set between 235 | Length |
| m ch | | | | | Set betweenft. | |
| 1000 | NALLEY | | 85 | | Gravel pack? X Size ro | |
| Dandy | 4 clay | | 91 | 151 | 11. Static water level:ft. below land su | mo./day/yr. ırface Date |
| m. Obracel | | | 15 | 158 | 12. Pumping level below lan | |
| Chandy Clay | | | | \$ 164 | ft. after | hrs. pumping g.p.m. |
| 4 dos | 2 7 3 | | | 181 | Estimated maximum yield | |
| yn H. O | | | | | V | mo./day/yr. Date |
| M. Chave | | | | 11192 | 14. Well head completion: Pitless adapter | 17 |
| 7. Chand | | | | 7215 | 15. Well grouted? US | Inches above grade |
| m. Chavel | | | | 5238 | With: X Neat cement | Bentonite Concrete |
| Clandy | 0000 | | | 3 243 | Depth: From ft. to 16. Nearest source of possible | le contamination: |
| (500) | | | 1 | | ft. 100 Direction 2 Well disinfected upon comple | Type Court |
| Och 2 34334 | | | | 3345 | 17. Pump: | Not installed |
| | | | | Manufacturer's name | HP Volts | |
| Market and | | | | Length of drop pipe | | |
| - Aliente of the | | | | | Type: Submersible | Turbine |
| | (Use a second s | set if needed) | | | Jet Centrifugal | Reciprocating Other |
| 18. Elevation: | 19. Remarks: | , | | | 20. Water well contractor's | |
| 1 | | | | | This well was drilled under m | ny jurisdiction and this report |
| Topography: | | | | | is true to the best of my knov | illuma 376 |
| Hill Slope | | | | | Business name | License No. |
| Upland | | | | | Signed Joseph B. | sipper Date 5-81 |
| Valley | | | | | Authorized rep | presentative |

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5