


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

AAA WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

Twp; Menlo

X Location of well:		County Thomas	Fraction NE 1/4 NE 1/4 NE 1/4	Section number 25	Township number T 8 S	Range number R 31 E/W
2. Distance and direction from nearest town or city: From Menlo, Ks. 1 mile south Street address of well location if in city:				3. Owner of well: Larry Ostmeyer R.R. or street: City, state, zip code: Menlo, Kansas		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 30 in. Completion date 4-16-76 Well depth 190 ft.		
				7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary		
5. Type and color of material		From	To	8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other		
Clay		0	52	9. Casing: Material Steel Height: Above or below Threaded Welded X Surface 12 in. RMP PVC Weight 7 gauge Dia. 16 in. to 121 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 0.188		
Medium to coarse sand		52	63	10. Screen: Manufacturer's name Brown 10' Cook Type Perforated Dia. 16" Slot/gauze 10% Length 60' Set between 121 ft. and 181 ft. 181 ft. and 191 ft. Gravel pack? X Size range of material 2X5/8 50%#1		
Clay		63	72	11. Static water level: 96 ft. below land surface Date 4-26-76		
Coarse sand & gravel		72	82	12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. 186 ft. after 2 hrs. pumping 670 g.p.m. Estimated maximum yield 670 g.p.m.		
Medium to coarse sand & layers of clay		82	100	13. Water sample submitted: Yes X No Date		
Clay		100	104	14. Well head completion: Pitless adapter 12 inches above grade		
Coarse sand & clay streaks		104	114	15. Well grouted? X With: Neat cement X Bentonite X Clay Depth: From 0 ft. to 10 ft.		
Coarse sand & gravel		114	119	16. Nearest source of possible contamination: ft. 600 Direction East Type Farm Well disinfected upon completion? Yes X No		
Clay		119	122	17. Pump: Not installed Manufacturer's name Floway Model number 7645 HP 60 Volts Length of drop pipe 180 ft. capacity 500 g.p.m. Type: 6 stage 10" DOH bowl Submersible X Turbine Jet Reciprocating Centrifugal Other		
Coarse sand & gravel		122	139	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Western Well & Pump Inc. 245 Business name License No. Address PO Box 852 Colby, Ks. Signed Sally Berry Date 5/11 Authorized representative		
Clay		139	158			
Medium to coarse sand & layers of clay		158	169			
Coarse sand & gravel		169	175			
Coarse sand & gravel & clay streaks		175	180			
Coarse sand & gravel		180	187			
Ochre & shale		187	200			
(Use a second sheet if needed)						
18. Elevation:	19. Remarks: BROCK 187'					
Topography: Hill Slope X Upland Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5