

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County <u>Thomas</u>	Fraction <u>6W 1/2 SW 1/4 NE 1/4</u>	Section number <u>27</u>	Township number T <u>8</u> S R <u>31</u> E <u>W</u>	Range number
2. Distance and direction from nearest town or city: Street address of well location if in city:	<u>1 1/2 miles NW</u>		3. Owner of well: <u>Al Dickman</u> R.R. or street: City, state, zip code: <u>Oakley, Ks. 67748</u>		
4. Locate with "X" in section below: N W E S 1 Mile	Sketch map: 		6. Bore hole dia. <u>2 1/2</u> in. Completion date <u>1/13/75</u> Well depth <u>206</u> ft.		
5. Type and color of material	From	To	7. ☒ Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
<u>Top clay limestone</u>	<u>0</u>	<u>100</u>	8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☒ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other		
<u>Rock</u>	<u>100</u>	<u>101</u>	9. Casing: Material <u>Asb-C</u> Height: Above or below Threaded ☐ Welded ☐ Surface <u>8</u> in. RMP ☐ PVC ☐ Weight <u>38.46</u> lbs./ft. Dia. <u>1 1/2</u> in. to <u>128</u> ft. depth Wall Thickness: inches or Dia. <u>1 1/2</u> in. to <u>128</u> ft. depth gauge No. <u>58</u>		
<u>sand</u>	<u>101</u>	<u>104</u>	10. Screen: Manufacturer's name <u>John Manswell</u> Type <u>Asb-C</u> Dia. <u>1 1/2</u> Slot/gauze <u>28</u> Length <u>28</u> Set between <u>128</u> ft. and <u>206</u> ft. ft. and <u>206</u> ft. Gravel pack? <u>yes</u> Size range of material <u>24</u>		
<u>sandy clay</u>	<u>104</u>	<u>112</u>	11. Static water level: <u>100</u> ft. below land surface Date <u>1/13/75</u> mo./day/yr.		
<u>sand</u>	<u>112</u>	<u>114</u>	12. Pumping level below land surfaces: <u>166</u> ft. after <u>4</u> hrs. pumping <u>800</u> g.p.m. ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>800</u> g.p.m.		
<u>sandy clay</u>	<u>114</u>	<u>119</u>	13. Water sample submitted: <u> </u> mo./day/yr. Yes ☒ No ☐ Date <u> </u>		
<u>sand</u>	<u>119</u>	<u>138</u>	14. Well head completion: <u> </u> Pitless adapter <u>8</u> Inches above grade		
<u>sandy clay</u>	<u>138</u>	<u>140</u>	15. Well grouted? <u>yes</u> With: ☒ Neat cement ☐ Bentonite ☐ Concrete Depth: From <u>0</u> ft. to <u>12</u> ft. <u>Asb-C</u>		
<u>sand + clay</u>	<u>140</u>	<u>150</u>	16. Nearest source of possible contamination: ft. <u>30</u> Direction <u>W</u> Type <u>Draw</u> Well disinfected upon completion? ☒ Yes ☐ No		
<u>sand</u>	<u>150</u>	<u>160</u>	17. Pump: <u> </u> Not installed Manufacturer's name <u>Western Hand Roller</u> Model number <u>Turbine</u> HP <u>100</u> Volts <u> </u> Length of drop pipe <u>130</u> ft. capacity <u>800</u> g.p.m. Type: ☐ Submersible ☒ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other		
<u>limestone</u>	<u>160</u>	<u>164</u>	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Corder Drilling</u> <u>114</u> Business name License No. Address <u>Golden, Ks.</u> Signed <u>Chas. Corder</u> Date <u>12-10-74</u> Authorized representative		
<u>sand</u>	<u>164</u>	<u>177</u>			
<u>sandy clay w/ sand</u>	<u>177</u>	<u>187</u>			
<u>limestone + clay to sandy</u>	<u>187</u>	<u>204</u>			
<u>sand</u>	<u>204</u>	<u>205</u>			
<u>shale</u>	<u>205</u>	<u>206</u>			
18. Elevation: Topography: ☐ Hill ☒ Slope ☐ Upland ☐ Valley	19. Remarks: <u>This well was dug in 1974 and the pump was set early in 1975. At which time the well was completed.</u> <u>2956 (TOP)</u>				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5